

County Surveyor's Record, Douglas County, Oregon

17052

South Boundary of T. 19 S., R. 9 W., Willamette Meridian

CHAINS

July 9, 1899.

I'm going to the NW cor. of sec. 2, T. 20 S., R. 9 W., to begin the survey of the S. Bdy. of T. 19 S., R. 9 W. I pass by the meridian determined by me at the NE cor. of T. 20 S., R. 10 W., and in order to test the adjustments of my instrument, at this cor. I set off 43° 52' on the lat. arc, and 22° 19 1/2' N. on the decl. arc., and at 4^h 9^m P.M. l.m.t. determine a true meridian with the solar. Which coincides with the meridian formerly established by me. I therefore conclude the adjustments are satisfactory.

July 9, 1899.

Survey commenced July 10, 1899, at 10^h 0^m A.M. l.m.t. I set off 43° 52' on the lat. arc and 22° 13' N. on decl. arc, and determine a true meridian with the solar, at the NW cor. of sec. 2, T. 20 S., R. 9 W., which is a post marked and witnessed as described by the Surveyor General.

Thence, I run west, along S. Bdy. of T. 19 S., R. 9 W., setting temporary 1/4 secs. and sec. cors., and at 320.87 chs. intersect the E. Bdy. of T. 19 S., R. 10 W., at a point 9.29 chs. N. of Tps. 19 and 20 S., R. 10 W., before described, and at point of intersection;

A chittam, 6 ins. diam., for closing cor. of Tps. 19 and 20 S., R. 9 W. I marked C.C. R. 9 W. on E., T. 20 S., Sec. 6 on S., and T. 19 S., Sec. 31 on N. sides with 6 notches on NE and S sides, from which:

A fir, 20 ins. diam., bears S. 26 3/4° E., 26 lks. dist., marked T20S R9W S6 BT.

A chittam, 6 ins. diam., bears N. 20° E., 40 lks. dist., marked T19S R9W S31 BT.

Thence I run East on S. Bdy. of sec. 31.

Ascend through second growth fir, timber, and dense undergrowth.

16.25

Top of spur 150 ft. above closing cor., bears SE. Descend 200 ft. to

40.00

in ravine, course SE, set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for 1/4 sec. cor. Marked 1/4 S31 on N. face, from which:

An alder, 7 ins. diam., bears N. 19° E., 12 lks. dist., marked 1/4S BT.

An alder, 7 ins. diam., bears N. 11° W., 13 lks. dist., marked 1/4S BT.