

County Surveyor's Record, Douglas County, Oregon

17053

South Boundary of T. 19 S., R. 9 W., Willamette Meridian

CHAINS	
	<p>The old 1/4 sec. cor. bears E. 5 lks. dist. I destroy it.</p> <p>Ascend 100 ft. to</p>
48.00	<p>Top of spur, bears S. Descend 100 ft. to</p>
65.25	<p>Ravine, course SE. Ascend 150 ft. to</p>
80.00	<p>Summit of ridge, bears NE & SW. Set a basalt stone 16 x 8 x 8 ins., 12 ins. in the ground for cor. of secs. 31 and 32. Marked with 5 notches on E. and 1 notch on W. edges, and raised a mound of stone, 2 ft. base, 1 1/2 ft. high W. of cor. No trees within limits.</p> <p>The old cor. bears East 7 lks. dist. I destroy it.</p> <p>Land; mountainous. Soil; sandy 3rd rate. Timber; fir, mostly burnt, with a second growth of small fir. Dense undergrowth of salal, salmon and thimbleberry. Mountainous, heavily timbered land, or land covered with dense undergrowth</p> <p style="text-align: right;">80.00 chains</p> <p style="text-align: right;">July 10 and 11, 1899.</p>
	<hr/> <p>July 12, 1899, at 7^h 0^m A.M. l.m.t. I set off 43° 52' on the lat. arc., and 21° 59' N. on decl. arc., and determine a true meridian with the solar at the cor. of secs. 31 and 32, on S. Bdy of Tp. Thence I run</p> <p>East on S. bdy. of sec. 32, descend through burnt timber and dense undergrowth.</p>
23.00	<p>Ravine, 200 ft. below sec. cor. course South. Ascend</p>
40.00	<p>Set a fir post 3 ft. long, 4 ins. sq., 24 ins. in the ground for the 1/4 sec. cor. Marked 1/4 S32 on N. face from which:</p> <p style="padding-left: 40px;">A fir, 4 ins. diam., bears N. 80° E., 10 lks. dist., marked 1/4S BT.</p> <p style="padding-left: 40px;">A hemlock, 4 ins. diam., bears N. 2° W., 25 lks. dist., marked 1/4S BT.</p>
	<p>The old 1/4 Sec. Cor bears E. 8 lks. dist. I destroy it.</p>
46.75	<p>Top of spur, 200 ft. above last ravine, bears SE. Descend 100 ft. to</p>
68.95	<p>Spring branch, 1 lk. wide, course SE. Ascend 75 ft. to</p>
80.00	<p>Set a fir post, 3 ft. long, 4 ins. sq., 24 ins. in the ground for cor. of secs. 32 and 33. Marked T19S S33 on NE face, and R9W S32 on NW face, with 4 notches on E. & 2 notches on W. edges, from which:</p> <p style="padding-left: 40px;">A fir, 6 ins. diam., bears N. 15° E., 20 lks. dist., marked T19S R9W S33 BT.</p> <p style="padding-left: 40px;">A fir, 8 ins. diam., bears N. 20° W., 10 lks. dist., marked T19S R9W S32 BT.</p> <p>The old cor. bears East, 4 lks. dist. I destroy it.</p>