

County Surveyor's Record, Douglas County, Oregon

17057

T. 22 S., R. 13 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of portions of the south boundary (Fifth standard Parallel South), east boundary, and subdivisional lines, and the subdivision of section 36, township 22 south, range 13 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this survey is as follows:

The boundaries and subdivisional lines of the township were surveyed by Harvey Gordon, U.S. Deputy Surveyor, in 1857.

The south boundary (Fifth Standard Parallel South) was resurveyed by Glenn F. Goodson, Rick E. Tawney, and John P. Lee, Cadastral Surveyors, in 1980.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1973, and the special instructions dated October 1, 1982, and the Amendment to Special Instructions dated October 20, 1982, for Group Number 1122, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations and refer to the true meridian.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and monumented at proportionate positions based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. Those lines not forming a closure were measured twice.

The geographic position of the 1/4 sec. corner of sections 13 and 14, as determined by a tie to triangulation station "GUARD", established by the Oregon State Highway Department in 1968, in the northwest one-quarter of section 13, is as follows:

Latitude 43° 39' 41.40" N. Longitude 124° 12' 08.87" W.

The mean magnetic declination is 19° 30' E.

Dependent Resurvey of a Portion of the South Boundary
(Fifth Standard Parallel South),
T. 22 S., R. 13 W., Willamette Meridian, Oregon

(Restoring the survey executed by Harvey Gordon in 1857, and the resurvey by Glenn F. Goodson, Rick E. Tawney, and John P. Lee in 1980)

Beginning at the standard cor. of Tps. 22 and 23 S., R. 13 W., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above the ground, with brass cap mkd.

T 22 S	T 23 S
R 13 W	R 12 W
36	
1	6
T 23 S	
R 13 W	