

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy.,
T. 22 S., R. 13 W., Willamette Meridian, Oregon

17058

CHAINS

from which the remains of the original bearing trees

A root hole, bears N. 41° E., 10 lks. dist.

A root hole, bears S. 22° E., 48 lks. dist.,
alongside of which is lying a fir, 18 ins. diam.,
with no marks visible on opened blaze.

A root hole, bears S. 85° W., 11 lks. dist.,
alongside of which is lying a fir, 24 ins. diam.,
with no marks visible.

A root hole, bears N. 6° W., 42 lks. dist.

and bearing trees by County Surveyors in 1949 and 1974

A cedar, 13 ins. diam., bears N. 83 1/2° E., 34 1/2 lks.
dist., with marks T23 R12 S6 BT visible on a
partially healed blaze.

A fir, 25 ins. diam., bears S. 86° W., 26 1/2 lks.
dist., mkd. with a healed blaze.

A fir, 34 ins. diam., bears N. 30° W., 74 lks. dist.,
mkd. with a healed blaze.

West, bet. secs. 1 and 36, marking the true line.

Descend 80 ft. over NW. slope, through moderate timber
and dense undergrowth.

2.60 Old U.S. Highway No. 101, asphalt surfaced, 30 lks. wide,
bears N. 30° E. curving E. and S. 30° W. curving E.

7.55 Clear Creek, 5 lks. wide, course S. 45° W.; asc. 70 ft.
over SE. slope.

10.65 Top of ascent, slopes S.; continue over broken NW. slope.

18.30 Leave timber and undergrowth, edge bears NE. and SW.;
enter open rolling sand dunes, through scattering timber
and undergrowth.

20.00 Point for the standard E 1/16 sec. cor. of secs. 1 and
36.

Set an aluminum rod, 24 ft. long, 5/8 in. diam., 23 ft.
in the ground, in concrete, with aluminum cap mkd.

S C
E 1/16 $\frac{S\ 36}{S\ 1}$
1982

from which

A pine, 16 ins. diam., bears N. 60° E., 265
lks. dist., mkd. E 1/16 S36 SC BT.

A spruce, 18 ins. diam., bears S. 80 3/4° W.,
485 lks. dist., mkd. E 1/16 SC BT.

Set a steel fence post, 6 ft. long, 2 ft. in the
ground alongside the aluminum rod.

Descend 90 ft. over open rolling sand dunes.

40.00 The standard 1/4 sec. cor. of secs. 1 and 36, monumented
with an aluminum post, 2 1/2 ins. diam., firmly set in con-
crete, projecting 7 ins. above the ground, with aluminum
cap mkd.