

# County Surveyor's Record, Douglas County, Oregon

17059

Dependent Resurvey, Portion of S. Bdy.,  
T. 22 S., R. 13 W., Willamette Meridian, Oregon

CHAINS	<p>S C T 22 S R 13 W 1/4 S 36 S 1 T 23 S 1980</p>
	<p>from which bearing trees by Goodson, Tawney, and Lee</p> <p>A pine, 8 ins. diam., bears S. 80° W., 73 1/2 lks. dist., with scribe marks 1/4 S1 SC BT visible on a partially healed blaze.</p> <p>A pine, 11 ins. diam., bears N. 62 1/2° W., 28 lks. dist., with scribe marks 1/4 S36 SC BT visible on a partially healed blaze.</p>
	<p>Dependent Resurvey of a Portion of the East Boundary T. 22 S., R. 13 W., Willamette Meridian, Oregon</p>
	<p>(Restoring the survey executed by Harvey Gordon in 1857)</p> <hr style="width: 20%; margin: auto;"/> <p>From the standard cor. of Tps. 22 and 23 S., R. 13 W. N. 0° 11' E., bet. secs. 6 and 36.</p> <p>Descend 60 ft. over broken NW. slope, through heavy timber and dense undergrowth.</p>
2.60	<p>Old Highway No. 101, asphalt surfaced, 30 lks. wide, bears N. 45° E. and S. 45° W.</p>
2.97	<p>Point for the closing cor. of Tps. 22 and 23 S., R. 12 W., at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.</p> <p>Continue bet. secs. 31 and 36.</p>
9.40	<p>Old Highway No. 101, asphalt surfaced, 30 lks. wide, bears N. 25° W. and S. 25° E.</p>
19.51	<p>From this point an iron pipe, 1 in. diam., firmly set flush with the ground, bears W., 2 lks. dist., established and recorded by William J. Brayton, Registered Professional Engineer No. 2793, Oregon, in 1953.</p>
20.185	<p>Point for the S 1/16 sec. cor. of secs. 31 and 36, occupied by a fir, 20 ins. diam. Mark the tree S 1/16 S36 on the W. face and S31 on the E. face.</p> <p>No bearing trees mkd. at the request of landowners.</p> <p>Descend 10 ft. over broken NW. slope.</p>
20.26	<p>From this point an iron pipe, 1 in. diam., firmly set flush with the ground, bears W., 3 lks. dist., established and recorded by William J. Brayton, Registered Professional Engineer No. 2793, Oregon, in 1953.</p>
40.37	<p>The 1/4 sec. cor. of secs. 31 and 36, established by person(s) unknown and perpetuated and recorded by Ronald E. Stuntzner, Registered Land Surveyor No. 1342, in 1979, monumented with an iron pipe, 1 in. diam., firmly set flush with surface of the ground, alongside of which is an iron rod, 5/8 in. diam., firmly set, projecting 4 ins.</p>