

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 22 S., R. 13 W., Willamette Meridian, Oregon

17065

CHAINS																										
80.50	<p style="text-align: center;">Set a steel fence post alongside the aluminum rod.</p> <p>Descend 250 ft. over rolling sand dunes.</p> <p>The cor. of secs. 25, 26, 35, and 36.</p> <p>Land, rolling. Soil, snad and sandy loam. Timber, spruce, fir, pine, and cedar; undergrowth, salal, huckleberry, rhododendron, manzanita, young timber, and willow.</p>																									
0.90	<p>From the cor. of secs. 13, 18, 19, and 24, on the E. bdy. of the Tp., perpetuated and recorded by Gregory Quibell, Deputy Douglas County Surveyor, in 1981, monumented with an iron post, 1 1/2 ins. diam., firmly set, projecting 6 ins. above the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td></td> <td></td> <td style="text-align: center;">T 22 S</td> <td></td> <td></td> </tr> <tr> <td style="text-align: center;">R</td> <td></td> <td style="text-align: center;">S 13</td> <td style="text-align: center;">S 18</td> <td style="text-align: center;">R</td> </tr> <tr> <td style="text-align: center;">13</td> <td style="text-align: center;"> </td> <td style="text-align: center;">S 24</td> <td style="text-align: center;">S 19</td> <td style="text-align: center;">12</td> </tr> <tr> <td style="text-align: center;">W</td> <td></td> <td></td> <td></td> <td style="text-align: center;">W</td> </tr> <tr> <td></td> <td></td> <td colspan="2" style="text-align: center;">1981</td> <td></td> </tr> </table> </div> <p>from which the remains of two original bearing trees</p> <p style="margin-left: 40px;">A rotted spruce stump, 46 ins. diam., bears S. 67° E., 68 lks. dist., with scribe marks 19 T visible on opened blaze. (Record, S. 72° E.)</p> <p style="margin-left: 40px;">A rotted spruce stump, 36 ins. diam., bears N. 22 1/2° W., 16 lks. dist., no marks visible. (Record, N. 15° W.)</p> <p>and bearing trees mkd. by Quibell in 1981</p> <p style="margin-left: 40px;">A spruce, 28 ins. diam., bears S. 7 1/4° E., 109 lks. dist., with scribe marks T22S R12W S19 SC BT visible on an open blaze.</p> <p style="margin-left: 40px;">A spruce, 20 ins. diam., bears S. 54 3/4° W., 54 lks. dist., with scribe marks T22S R13W S24 CS BT visible on partially healed blaze.</p> <p style="margin-left: 40px;">A fir, 19 ins. diam., bears N. 27 1/4° W., 46 lks. dist., with scribe marks T22S R13W S13 CS BT visible on partially healed blaze.</p> <p>and a new bearing tree</p> <p style="margin-left: 40px;">A spruce, 23 ins. diam., bears N. 60 3/4° E., 125 lks. dist., mkd. T22S R12W S18 BT.</p> <p>N. 89° 20' W., bet. secs. 13 and 24.</p> <p>Descend 10 ft. over SW. slope, through scattered timber and dense undergrowth.</p>			T 22 S			R		S 13	S 18	R	13		S 24	S 19	12	W				W			1981		
		T 22 S																								
R		S 13	S 18	R																						
13		S 24	S 19	12																						
W				W																						
		1981																								
4.60	<p>Ravine, drains S.; asc. 25 ft. over SE. slope.</p>																									
7.10	<p>Top of ascend, slopes S.; desc. 30 ft. over SW. slope.</p>																									
7.22	<p>East edge of Clear Lake, bears N. 40° W. and S. 40° E.</p> <p>Point for the meander cor. of secs. 13 and 24, at record dist., falls in Clear Lake.</p>																									