

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 22 S., R. 13 W., Willamette Meridian, Oregon

17068

CHAINS	
30.08	<p>From this point, an iron pipe, 1 in. diam., firmly set flush with the surface of the ground, bears West, 2 lks. dist., established and recorded by John E. Hollingsworth, Registered Land Surveyor No. 691, Oregon, in 1977.</p>
39.79	<p>The 1/4 sec. cor. of secs. 13 and 14, monumented with an iron pipe, 1 in. diam., firmly set flush with the surface of the ground, reestablished and recorded by John E. Hollingsworth, Registered Land Surveyor No. 691, Oregon, in 1977, and is accepted as the best available evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, in concrete, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 13 W 1/4 S 14 S 13 1982</p> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside the iron post.</p> <p>From this point, Oregon State Highway Department triangulation station "GUARD", 1968, bears N. 57° 51' E., 23.73 chs. dist., monumented with a standard brass tablet, 3 1/4 ins. diam., set in a concrete post, 9 ins. diam., firmly set, projecting 9 ins. above the ground, mkd. GUARD 1968.</p>
5.00	<p>From the cor. of secs. 25, 26, 35, and 36.</p> <p>West, on record bearing bet. secs. 26 and 35.</p> <p>Descend slightly over open rolling sand dunes.</p> <p>Enter moderate timber and undergrowth, edge bears NW. and SE.</p>
11.00	<p>Leave timber and undergrowth, edge bears N. and S.</p>
40.00	<p>Point for the 1/4 sec. cor. of secs. 26 and 35, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.</p> <p style="text-align: center;">T 22 S R 13 W 1/4 S 26 S 35 1982</p> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside the iron post.</p> <p>Continue over rolling sand dunes.</p>
41.40	<p>Point selected for the witness cor. to the meander cor. of secs. 26 and 35.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.</p>