

County Surveyor's Record, Douglas County, Oregon

17070

Subdivision of Sec. 36,
T. 22 S., R. 13 W., Willamette Meridian, Oregon

CHAINS	
20.05	<p>Point for the center S 1/16 sec. cor. of sec. 36.</p> <p>Set an aluminum rod, 19 ft. long, 5/8 in. diam., 18 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} C \\ S\ 1/16 \quad \quad S\ 36 \\ C \\ 1982 \end{array}$ </div> <p>No suitable trees available within limits.</p> <p>Set a steel fence post alongside the aluminum rod.</p> <p>Ascend 60 ft. over open rolling sand dunes.</p>
40.10	<p>Point for the center 1/4 sec. cor. of sec. 36, at the intersection with the E. and W. center line.</p> <p>Set an aluminum rod, 19 ft. long, 5/8 in. diam., 18 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> $\begin{array}{c} T\ 22\ S \quad R\ 13\ W \\ C\ 1/4 \quad S\ 36 \\ 1982 \end{array}$ </div> <p>from which</p> <p style="padding-left: 40px;">A fir, 15 ins. diam., bears N. 28° E., 659 1/2 lks. dist., mkd. C 1/4 S36 BT.</p> <p>No suitable tree available to the E. within limits.</p> <p>Set a steel fence post alongside the aluminum rod.</p> <p>Ascend 80 ft. over open rolling sand dunes.</p>
79.94	<p>The 1/4 sec. cor. of secs. 25 and 36.</p>
	<p>From the 1/4 sec. cor. of secs. 31 and 36, on the E. bdy. of the Tp.</p> <p>S. 89° 36' W., on the E. and W. center line of sec. 36.</p> <p>Descend slightly over NW. slope, through moderate timber and dense undergrowth.</p>
4.90	<p>Old Highway No. 101, asphalt surfaced, 30 lks. wide, bears N. 40° W. curving W. and S. 40° E. curving W.</p>
5.495	<p>From this point an iron rod, 5/8 in. diam., firmly set 1 1/2 ft. below the ground surface, bears North, 5 1/2 lks. dist., established and recorded by Roy H. Erichsen, Registered Engineer No. 2740, Oregon, in 1964.</p>
6.05	<p>Clear Creek, 5 lks. wide, course S. 15° E.; asc. 30 ft. over E. slope.</p>
13.50	<p>Top of ascent, slopes N.; desc. 25 ft. over broken NW. slope.</p>
20.09	<p>Point for the center E 1/16 sec. cor. of sec. 36.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.</p>