

County Surveyor's Record, Douglas County, Oregon

17075

T. 29 S. R. 9 W. Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the north and east boundaries, township 30 south, range 10 west, a portion of the south boundary and subdivisional lines, and subdivision of sections 11 and 31, and the remonumentation of certain original corner points, township 29 south, range 9 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey is as follows:

A portion of the south boundary and subdivisional lines of the township, was surveyed by Dennis Hathorn, U.S. Deputy Surveyor, in 1856.

A portion of the subdivisional lines was surveyed by William S. Chapman, U.S. Deputy Surveyor, in 1875.

A portion of the east boundary and subdivisional lines of township 29 south, range 10 west, were surveyed by William P. Wright, U.S. Deputy Surveyor, in 1880.

The corner of sections 5, 6, 31, and 32, on the south boundary of the township, was remonumented by William M. Bushey, U.S. Deputy Surveyor, in 1893, during the course of the subdivision of township 30 south, range 9 west.

A portion of the south boundary of the township was retraced, a portion of the west boundary was resurveyed, and the survey of the west boundary and subdivisional lines was completed by William M. Porter, U.S. Deputy Surveyor, in 1907-09.

Those portions of the north and east boundaries of section 1, township 30 south, range 10 west, connecting the Hathorn corner of townships 29 and 30 south, range 9 west, with the Wright corner of townships 29 south, ranges 9 and 10 west, were surveyed by William M. Porter, U.S. Deputy Surveyor, in 1909, and the northeast corner of section 1, township 30 south, range 10 west was established.

A portion of the east boundary and subdivisional lines, township 29 south, range 10 west, was retraced, and the subdivisional lines for township 29 south, range 10 west, were completed by William N. Gibb, U.S. Deputy Surveyor, in 1909-10.

The corner of sections 5, 6, 31, and 32, townships 29 and 30 south, range 9 west, was remonumented by James E. Jelley, Cadastral Surveyor, in 1962.

A portion of the subdivisional lines were resurveyed and certain original corner points were remonumented without survey by John M. Jelley, Cadastral Surveyor, in 1966.

Certain original corner points were remonumented, without survey, by Jack W. Bowder, Cadastral Surveyor, in 1977-78.

The resurvey and remonumentation were executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, Special instructions dated July 13, 1979, under Group Number 1000, Oregon, Special Instructions dated April 6, 1979, and Supplemental Special Instructions dated July 20, 1979.