

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy.,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17078

CHAINS

A decayed cedar stump, 45 ins. diam., bears S. 25° W., 81 lks. dist., no marks visible on decayed blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

1/4 S 6
T 30 S R 9 W
1982

from which new bearing trees

A fir, 14 ins. diam., bears S. 44 1/2° E., 21 lks. dist., mkd. 1/4 S6 BT.

A hemlock, 8 ins. diam., bears S. 59 3/4° W., 54 lks. dist., mkd. 1/4 S6 BT.

N. 89° 51' W., beginning new measurement.

Descend 305 ft. over broken W. slope.

18.31

Point for the W 1/16 sec. cor. of sec. 31 only.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16 S 31
1982

from which

A hemlock, 34 ins. diam., bears N. 74° W., 86 1/2 lks. dist., mkd. W 1/16 S31 BT.

An alder, 9 ins. diam., bears N. 22 1/4° W., 29 lks. dist., mkd. W 1/16 S31 BT.

Descend 120 ft. over W. slope.

21.15

Creek, 5 lks. wide, course S. 15° W.; asc. 185 ft. over SE. slope.

31.50

Spur ridge, bears N. and S.; desc. 165 ft. over SW. slope.

40.07

The cor. of Tps, 29 and 30 S., R. 9 W., on the E. bdy. of T. 30 S., R. 10 W., recovered and recorded by Bruce A. Shaner, Registered Land Surveyor, No. 430, in 1963, monumented with the original sandstone, 32 x 32 ins., firmly set, projecting 18 ins. above ground, with chisel marks 30S and 6 grooves on S., 29S and 6 grooves N., and CC on E. faces, from which the original bearing objects

A sandstone, 5 x 5 x 4 ft. above ground, bears N. 68° E., 28 lks. dist., with marks X B0 visible.

A sandstone, 3 x 2 x 1 ft. above ground, bears S. 70° E., 22 lks. dist., with marks X B0 visible. (Record, 20 lks..)

At the corner point