

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of S. Bdy.,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17079

CHAINS

Set a brass tablet, 3 1/4 ins. diam., 3 1/2 ins. stem, in drill hole in corner stone., mkd.

		T 29 S
		R 9 W
T 30 S		S 31
R 10 W		S 6
S 1		T 30 S
		1979

from which

A fir, 20 ins. diam., bears S. 52° E., 19 lks.  
dist., mkd. T30S R9W S6 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, hemlock, cedar, alder, maple, chinquapin, and madrone; undergrowth, salal, rhododendron, huckleberry, Oregon grape, salmonberry, poison oak, and fern.

Dependent Resurvey of a Portion of the East Boundary,  
T. 30 S., R. 10 W., Willamette Meridian, Oregon

(Restoring the survey by William M. Porter in 1909)

From the cor. of Tps, 29 and 30 S., R. 9 W.

N. 0° 03' E., on the E. bdy. of sec. 1.

Ascend 70 ft. over SW. slope, through heavy timber and dense undergrowth.

1.97

The NE. cor. of T. 30 S., R. 10 W., perpetuated and recorded by Bruce A. Shaner, Registered Land Surveyor No. 430, in 1963, monumented with the original sandstone, 22 x 17 x 6 ins., firmly set, projecting 10 ins. above ground, mkd. with 6 grooves on the S. and W. faces, from which a bearing tree mkd. by Shaner

A fir, 20 ins. diam., bears S. 33° W., 52 lks.  
dist., with healed blaze.

and bearing trees mkd. by person(s) unknown

A chinquapin, 6 ins. diam., bears S. 70° W.,  
15 lks. dist., no marks visible on decayed blaze.

A fir, 19 ins. diam., bears S. 87 1/2° W., 34 lks.  
dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S	R 9 W
	S 31
T 30 S	
R 10 W	
S 1	
	1979

Deposit corner stone alongside iron post.