

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17081

CHAINS

from which new bearing trees

A fir, 5 ins. diam., bears S. 78 1/2° E., 104 1/2 lks.
dist., mkd. 1/4 S32 BT.

A cedar, 17 ins. diam., bears N. 16° W., 39 lks.
dist., mkd. 1/4 S31 BT.

N. 0° 05' E., beginning new measurement.

Ascend 180 ft. over SE. slope.

19.60 Dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.

19.95 Point for the N 1/16 sec. cor. of secs. 31 and 32.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 20
ins. in the ground, to bedrock, and in a mound of stone,
2 ft. base, to top, with aluminum cap mkd.

N 1/16
S 31 | S 32
1982

from which

A fir stump, 29 ins. diam., bears N. 3/4° E.,
103 lks. dist., mkd. N 1/16 S32 BT.

A fir stump, 26 ins. diam., bears N. 42 1/4° W.,
32 lks. dist., mkd. N 1/16 S31 BT.

No suitable trees available.

Ascend 15 ft. over SE. slope.

24.75 Spur ridge, bears E. and S. 70° W.; desc. 325 ft. over
NW. slope.

30.10 Gravelled road, 25 lks. wide, bears N. 75° E. and
S. 75° W.

39.90 The cor. of secs. 29, 30, 31, and 32, monumented with an
iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins.
above ground, with brass cap mkd.

T 29 S R 9 W
S 30 | S 29
S 31 | S 32
1978

from which the remains of the original bearing trees

A sawed fir stump, 42 ins. diam., bears N. 50° E.,
85 lks. dist., with healed blaze.

A sawed fir stump, 26 ins. diam., bears S. 22° E.,
16 lks. dist., with healed blaze.

A sawed fir stump, 22 ins. diam., bears S. 35° W.,
27 lks. dist., with scribe marks W 9 29 W visible
on opened blaze.

A sawed fir stump, 26 ins. diam., bears N. 47° W.,
97 lks. dist., with healed blaze.

The cor. is located in logged area, no suitable trees
available.