

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17082

CHAINS

Land, mountainous.
Soil, rocky clay.
Timber, fir, hemlock, cedar, chinquapin, alder, maple,
and madrone; undergrowth, salal, rhododendron, black-
berry, huckleberry, vine maple, and fern.

S. 89° 56' W., bet. secs. 30 and 31.

Descend 195 ft. over a broken NW. slope, across logged
area, through moderate undergrowth.

19.91

The E 1/16 sec. cor. of secs. 30 and 31, established and
recorded by Arthur R. Evans, Registered Professional
Engineer No. 2741, in 1953, and is accepted as the
corner, monumented with an iron pipe, 3/4 in. diam.,
firmly set, projecting 4 ins. above ground, from which
the remains of bearing trees mkd. by Evans

A sawed fir stump, 30 ins. diam., bears N. 47° E.,
56 lks. dist., with healed blaze.

A sawed fir stump, 36 ins. diam., bears S. 55° E.,
49 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, directly over the iron pipe, with brass cap mkd.

E 1/16 $\frac{S\ 30}{S\ 31}$
 1979

from which new bearing trees

A chinquapin, 13 ins. diam., bears N. 29 1/2° E.,
42 lks. dist., mkd. E 1/16 S 30 BT.

A fir, 6 ins. diam., bears S. 38 1/4° W., 132 1/2 lks.
dist., mkd. E 1/16 S31 BT.

S. 89° 54' W., beginning new measurement.

Descend 260 ft. over broken NW. slope.

18.30

Gravelled road, 20 lks. wide, bears N. 10° E. and
S. 10° W.

19.89

The 1/4 sec. cor. of secs. 30 and 31, reestablished by pro-
portionate measurement and recorded by Arthur R. Evans,
Registered Professional Engineer No. 2741, in 1953, and
is accepted as the best available evidence of the posi-
tion of the original corner, further perpetuated and
recorded by Forrest J. LaFlamme, Registered Land Surveyor
No. 473, in 1963, determined from the remains of a bear-
ing tree mkd. by Evans

A sawed fir stump, 29 ins. diam., bears S. 36 1/2° E.,
23 lks. dist., with scribe marks BT visible on
opened blaze.

and the remains of a bearing tree mkd. by LaFlamme

A sawed fir stump, 33 ins. diam., bears N. 80 1/2° W.,
74 1/2 lks. dist., with scribe marks 1/4 S30 BT
visible on open blaze.