

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17083

CHAINS

and the remains of a bearing tree mkd. by person(s)  
unknown

A hemlock snag, 10 ins. diam., bears N. 53° W.,  
56 1/2 lks. dist., with scribe marks 1/4 S30 BT  
visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, with brass cap mkd.

T 29 S    R 9 W  
          1/4  $\frac{S 30}{S 31}$   
          1979

from which new bearing trees

A cedar, 12 ins. diam., bears S. 19° E., 48 1/2 lks.  
dist., mkd. 1/4 S31 BT.

A cedar, 5 ins. diam., bears N. 70 1/4° W., 51 lks.  
dist., mkd. 1/4 S30 BT.

N. 89° 54' W., beginning new measurement.

Descend 20 ft. over NW. slope.

1.00      Ravine, drains N.; asc. 75 ft. over broken NE. slope.

19.93      The W 1/16 sec. cor. of secs. 30 and 31, established and  
recorded by Arthur R. Evans, Registered Professional  
Engineer No. 2741, in 1953, and is accepted as the cor-  
ner, monumented with an iron pipe, 3/4 in. diam., firmly  
set, projecting 4 ins. above ground, from which the  
remains of bearing trees mkd. by Evans

A sawed fir stump, 37 ins. diam., bears N. 1° E.,  
30 lks. dist., with healed blaze.

A sawed fir stump, 33 ins. diam., bears S. 61° E.,  
24 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in  
the ground, directly over the iron pipe, with brass cap mkd.

W 1/16     $\frac{S 30}{S 31}$   
          1979

from which new bearing trees

A hemlock, 12 ins. diam., bears S. 8 1/2° W., 31 1/2  
lks. dist., mkd. W 1/16 S31 BT.

A hemlock, 8 ins. diam., bears N. 78 3/4° W.,  
20 1/2 lks. dist., mkd. W 1/16 S30 BT.

S. 89° 51' W., beginning new measurement.

Ascend 35 ft. over broken NE. slope.