

# County Surveyor's Record, Douglas County, Oregon

17085

Subdivision of Sec. 11,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 29 S R 9 W

$\frac{S 11}{S 14} 1/4$

BLM  
1966 1957

from which the original bearing trees

A fir, 44 ins. diam., bears North, 64 lks. dist., with scribe marks 1/4 S11 BT on bark and healed blaze at base.

A fir, 29 ins. diam., bears S. 17° W., 40 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Byron

A fir, 16 ins. diam., bears South, 53 lks. dist., with healed double blaze.

A hemlock stump, 8 ins. diam., bears N. 49° W., 4 1/2 lks. dist., with scribe marks BT visible on open blaze.

N. 0° 17' E., on the N. and S. center line of sec. 11.

Ascend 165 ft. over SW. slope, through heavy timber and dense undergrowth.

5.00 Leave old growth timber; enter young timber, edge bears N. 40° W. and S. 40° E.

5.50 Spur, slopes S. 25° E.; desc. 10 ft. over NE. slope.

8.85 Head of ravine, drains S. 80° E.; asc. 95 ft. over SE. slope.

12.90 Spur, slopes E.; desc. 25 ft. over NE. slope.

15.35 Ravine, drains E.; asc. 85 ft. over SE. slope.

19.60 Spur, slopes E.; desc. 150 ft. over NE. slope.

25.70 Ravine, drains S. 70° E.; asc. 140 ft. over SE. slope.

27.80 Enter old growth timber, leave young timber, edge bears N. 70° E. and S. 70° W.

31.30 Spur, slopes S. 85° E.; desc. 155 ft. over NE. slope.

35.10 Ravine, drains N. 70° E.; asc. 75 ft. over SE. slope.

38.10 Spur, slopes N. 80° E.; desc. 110 ft. over NE. slope.

40.32 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 29 S R 9 W  
C 1/4 S 11  
1979

from which

A hemlock, 8 ins. diam., bears N. 64 3/4° E., 18 lks. dist., mkd. C 1/4 S11 BT.