

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 11,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17086

CHAINS	
	<p>A hemlock, 9 ins. diam., bears S. 55 1/2° W., 30 lks. dist., mkd. C 1/4 S11 BT.</p> <p>Descend 140 ft. over NE. slope.</p>
45.35	Creek, 2 lks. wide, course S. 80° E.; asc. 595 ft. over SE. slope.
56.45	Slope, changes to SW. slope.
60.44	<p>Point for the center N 1/16 sec. cor. of sec. 11.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <math display="block">\begin{array}{c} C \\ N\ 1/16 \quad   \quad S\ 11 \\ C \\ 1979 \end{array}</math> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears S. 70° E., 24 lks. dist., mkd. CN 1/16 S11 BT.</p> <p style="margin-left: 40px;">A fir, 9 ins. diam., bears N. 19 1/2° W., 21 1/2 lks. dist., mkd. CN 1/16 S11 BT.</p> <p>Ascend 15 ft. over SW. slope.</p>
61.35	Spur, slopes E.; desc. 250 ft. over NW. slope.
71.20	Spur, slopes N. 20° E.; desc. 195 ft. over NW. slope.
80.56	<p>The 1/4 sec. cor. of secs. 2 and 11, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>COUNTY SURVEYORS OFFICE</p> <p>T 29 S R 9 W</p> <p>1/4 <math>\frac{S\ 2}{S\ 11}</math></p> <p>BLM</p> <p>1966</p> <p>1959</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir, 70 ins. diam., bears S. 55° W., 18 lks. dist., with scribe marks 1/4 S 1/4 S11 on bark.</p> <p style="margin-left: 40px;">A sawed fir stump, 40 ins. diam., bears N. 58° W., 86 lks. dist., with scribe marks 1/4 S 1/4 S2 on bark.</p> <p>and bearing trees mkd. by Byron</p> <p style="margin-left: 40px;">A hemlock, 15 ins. diam., bears N. 52° E., 34 lks. dist., with healed double blaze.</p> <p style="margin-left: 40px;">A cedar, 12 ins. diam., bears S. 32° E., 41 lks. dist., with illegible scribe marks visible on partially healed blaze.</p>