

County Surveyor's Record, Douglas County, Oregon

17087

Subdivision of Sec. 11,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from the 1/4 sec. cor. of secs. 11 and 12, perpetuated and recorded by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S | S
11 | 12
1/4
T 29 S R 9 W
1958

BLM 1966

from which the remains of the original bearing trees

A sawed fir stump, size indeterminate, bears N. 78° E., 12 lks. dist., with scribe mark B visible on opened decayed blaze.

A root hole, bears S. 77° W., 36 lks. dist., with downed fir, 24 ins. diam., alongside, no marks visible.

and bearing trees mkd. by Byron

A white fir, 18 ins. diam., bears S. 32° E., 52 lks. dist., with healed double blaze.

A white fir, 15 ins. diam., bears S. 59 1/2° W., 29 lks. dist., with healed double blaze.

S. 89° 51' W., on the E. and W. center line of sec. 11.

Ascend 135 ft. over NE. slope, through heavy timber and dense undergrowth.

- 2.95 Spur, slopes S. 30° E.; desc. 145 ft. along broken SW. slope.
- 25.60 Bottom of descent, drains S.; asc. 40 ft. over SE. slope.
- 28.05 Spur, slopes S. 40° E.; desc. 45 ft. over SW. slope.
- 28.75 Creek, 1 lk. wide, course S. 25° E.; asc. 195 ft. along NE. slope.
- 39.90 The center 1/4 sec. cor. of sec. 11.
Descend 120 ft. over NE. slope.
- 48.25 Spur, slopes N.; desc. 55 ft. over NW. slope.
- 52.80 Creek, 1 lk. wide, course N. 60° E.; asc. 240 ft. over precipitous SE. slope.
- 64.90 Spur, slopes S. 20° E.; desc. 60 ft. over SW. slope.
- 66.50 Ravine, drains S. 50° E.; asc. 300 ft. over NE. slope.
- 72.45 Spur, slopes S. 65° W.; asc. 275 ft. over SE. slope.
- 79.20 The 1/4 sec. cor. of secs. 10 and 11, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.

T 29 S R 9 W
1/4
S 10 | S 11
1966