

County Surveyor's Record, Douglas County, Oregon

17088

Subdivision of Sec. 11,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

from which the bearing trees mkd. by Jelley in 1966

A hemlock, 18 ins. diam., bears N. 83° E., 31 lks. dist., with healed blaze.

A fir, 20 ins. diam., bears N. 39° W., 18 lks. dist., with healed blaze.

The cor. is located in E. edge of logged area, edge bears N. and S.

From the N 1/16 sec. cor. of secs. 11 and 12, monumented with an iron post, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

N 1/16
S 11 | S 12
1966

from which the bearing trees mkd. by Jelley in 1966

A cedar, 14 ins. diam., bears N. 82° E., 29 lks. dist., with healed blaze.

A fir, 12 ins. diam., bears N. 21° W., 23 lks. dist., with healed blaze.

S. 89° 57' W., on the E. and W. center line of the NE 1/4 of sec. 11.

Ascend 140 ft. over NE. slope, through heavy timber and dense undergrowth.

3.70 Spur, slopes N. 10° E.; desc. 45 ft. over NW. slope.

7.70 Ravine, drains N. 50° E.; asc. 80 ft. over SE. slope.

9.50 Spur, slopes N. 20° E.; asc. 120 ft. over NE. slope.

26.30 Ravine, drains N. 75° E.; asc. 80 ft. along a S. slope.

28.45 Ravine, drains S. 50° E.; asc. 485 ft. over NE. slope.

38.90 Spur, slopes S. 40° E.; desc. 5 ft. over SW. slope.

39.94 The center N 1/16 sec. cor. of sec. 11.

Subdivision of Section 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

From the 1/4 sec. cor. of sec. 31 only, on the S. bdy. of the Tp.

N. 0° 22' W., on the N. and S. center line of sec. 31.

Descend 130 ft. over broken W. slope, through moderate timber and undergrowth.

12.20 Creek, 2 lks. wide, course S. 40° W.; asc. 120 ft. over broken SE. slope.

20.13 Point for the center S 1/16 sec. cor. of sec. 31.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.