

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17089

CHAINS

$$\begin{array}{c} C \\ S\ 1/16\ | S\ 31 \\ C \\ 1982 \end{array}$$

from which

A fir, 9 ins. diam., bears N. 73 1/2° E., 10 lks. dist., mkd. CS 1/16 S31 BT.

A hemlock, 18 ins. diam., bears N. 69 1/2° W., 12 lks. dist., mkd. CS 1/16 S31 BT.

From this point, a point established and recorded by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1968, bears N. 89° 45' W., 0.45 chs. dist., monumented with a wood post, 4 x 4 ins. sq., loosely set, projecting 24 ins. above ground, from which the remains of bearing trees mkd. by LaFlamme

A hemlock, 18 ins. diam., bears S. 86° E., 24 1/2 lks. dist., with scribe marks 6 S31 BT visible on partially healed blaze.

A root hole, bears S. 52° W., 30 lks. dist., alongside of which is a downed hemlock, 18 ins. diam., with scribe marks 1/16 S31 BT visible on open blaze.

Ascend 10 ft. over SE. slope.

21.60 Top of ascent, slopes W.; desc. 150 ft. over broken NW. slope.

31.60 Creek, 3 lks. wide, course S. 70° W.; asc. 150 ft. over broken S. slope.

40.26 Point for the center 1/4 sec. cor. of sec. 31, at intersection with the E. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} T\ 29\ S\ R\ 9\ W \\ C\ 1/4\ S\ 31 \\ 1982 \end{array}$$

from which

A fir, 23 ins. diam., bears N. 35 1/2° E., 33 lks. dist., mkd. X BT.

A fir, 15 ins. diam., bears N. 89 1/4° W., 6 1/2 lks. dist., mkd. C 1/4 S31 BT.

From this point, a point established and recorded by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1968, bears N. 88° 28' W., 0.34 chs. dist., monumented with a wood post, 4 x 4 ins. sq., loosely set, projecting 28 ins. above ground, from which bearing trees mkd. by LaFlamme

A fir, 18 ins. diam., bears N. 26° E., 30 lks. dist., with healed blaze.

A fir, 22 ins. diam., bears N. 85° W., 23 lks. dist., with healed blaze.