

County Surveyor's Record, Douglas County, Oregon

17090

Subdivision of Sec. 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 180. ft. over S. slope.
50.15	Spur ridge, bears E. and W.; desc. 105 ft. over broken W. slope.
60.25	Point for the center N 1/16 sec. cor. of sec. 31. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 31 \\ C \\ 1982 \end{array}$ </div> from which A cedar, 10 ins. diam., bears N. 57° E., 55 1/2 lks. dist., mkd. CN 1/16 S31 BT. A fir, 23 ins. diam., bears S. 13 1/4° E., 68 lks. dist., mkd. CN 1/16 S31 BT. The cor. is located at bottom of descent, slopes W. Ascend 10 ft. over SW. slope.
61.45	Top of ascent, slopes NW.; desc. 420 ft. over broken NW. slope.
77.20	Gravelled road, 25 lks. wide, bears N. 80° E. and N. 80° W. in curve.
80.24	The 1/4 sec. cor. of secs. 30 and 31.
	From the 1/4 sec. cor. of secs. 31 and 32. S. 89° 46' W., on the E. and W. center line of sec. 31. Descend 160 ft. over broken S. slope, across logged area, through moderate undergrowth.
4.90	Enter timber, edge bears N. 10° E. and S. 10° W.
19.74	Point for the center E 1/16 sec. cor. of sec. 31. Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. <div style="text-align: center;"> $\begin{array}{c} C \quad E\ 1/16 \\ \quad \quad S\ 31 \\ C \quad \quad \quad C \\ \quad \quad \quad 1982 \end{array}$ </div> from which A fir, 19 ins. diam., bears S. 75 1/2° E., 27 1/2 lks. dist., mkd. CE 1/16 S31 BT. A fir, 10 ins. diam., bears N. 27 1/2° W., 29 lks. dist., mkd. X BT. From this point, a point established and recorded by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1968, bears N. 87° 44' W., 0.175 chs. dist., monumented with a wood post, 4 x 4 ins. sq., firmly set, projecting 36 ins. above ground, from which bearing trees mkd. by LaFlamme