

# County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 31,  
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17091

| CHAINS |  |
|--------|--|
|        | <p>A fir, 13 ins. diam., bears N. 9° E., 19 lks. dist., with healed blaze.</p> <p>A fir, 15 ins. diam., bears S. 27° E., 2 lks. dist., with healed blaze.</p> <p>Descend 130 ft. over broken S. slope.</p>   |
| 35.45  | Creek, 2 lks. wide, course S. 45° W.; asc. 40 ft. over broken S. slope.  |
| 39.48  | <p>The center 1/4 sec. cor. of sec. 31.</p> <p>Ascend 5 ft. over S. slope.</p>   |
| 41.60  | Top of ascent, slopes S.; desc. 60 ft. over SW. slope.   |
| 43.50  | Creek, 1 lk. wide, course S.; asc. 35 ft. over broken S. slope.  |
| 48.70  | Top of ascent, slopes SE.; desc. 75 ft. over SW. slope.  |
| 53.30  | Creek, 1 lk. wide, course S. 20° W.; asc. 85 ft. over SE. slope.   |
| 59.07  | <p>Point for the center W 1/16 sec. cor. of sec. 31.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>C    <math>\frac{W \ 1/16}{S \ 31}</math>    C</p> <p>1982</p> </div> <p>from which</p> <p>A fir, 17 ins. diam., bears S. 41° W., 72 lks. dist., mkd. CW 1/16 S31 BT.</p> <p>A cedar, 9 ins. diam., bears N. 4 1/2° W., 22 lks. dist., mkd. CW 1/16 S31 BT.</p> <p>From this point, a point established and recorded by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1968, bears N. 75° 10' W., 0.21 chs. dist., monumented with a wood post, 4 x 4 ins. sq., firmly set, projecting 5 ft. above ground, from which bearing trees mkd. by LaFlamme</p> <p>A fir, 23 ins. diam., bears S. 83° E., 29 1/2 lks. dist., with healed blaze.</p> <p>A fir, 17 ins. diam., bears N. 30° W., 29 dist., with illegible scribe marks visible on partially healed blaze.</p> <p>Ascend 50 ft. over SE. slope.</p> |
| 69.20  | Spur ridge, bears N. 70° E. and S. 70° W.; desc. 105 ft. over NW. slope.   |
| 82.88  | <p>The original 1/4 sec. cor. of sec. 31 only, perpetuated and recorded by Forrest J. LaFlamme, Registered Land Surveyor No. 473, in 1968, monumented with an iron pipe, 1 1/4 ins. diam., firmly set, projecting 8 ins. above ground, from which the remains of an original bearing tree</p> <p>A decayed hemlock stump, size indeterminate, bears S. 88° E., 22 lks. dist., no marks visible.</p>  |