

County Surveyor's Record, Douglas County, Oregon

Subdivision of Sec. 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

17092

CHAINS

and the remains of bearing trees mkd. by LaFlamme

A cedar stump, 22 ins. diam., bears N. 47 1/2° E.,
51 lks. dist., with scribe marks 1/4 S31 BT
visible on open blaze.

A cedar, 42 ins. diam., bears N. 9° W., 10 lks.
dist., with scribe marks 1/4 S BT 473 visible
on partially healed blaze.

Continue over nearly level W. slope.

82.96

Intersect the E. bdy. of T. 29 S., R. 10 W., true point
for the 1/4 sec. cor. of sec. 31 only.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in
the ground, with brass cap mkd.

T 29 S
R 10 W | R 9 W
 ↓ 1/4 S 31
 1979

from which

A hemlock, 7 ins. diam., bears N. 48° E., 49 lks.
dist., mkd. 1/4 S31 BT.

A fir, 9 ins. diam., bears S. 59 1/2° E., 15 1/2 lks.
dist., mkd. 1/4 S31 BT.

From this point, the 1/4 sec. cor. of sec. 36 only, on the
E. bdy. of T. 29 S., R. 10 W., bears N. 0° 45' W., 1.99
chs. dist., described in the field notes of the dependent
resurvey of a portion of the E. bdy. of T. 29 S., R. 10
W., executed concurrently under these same groups and
Group No. 1067.

From the center E 1/16 sec. cor. of sec. 31.

N. 0° 10' W., on the N. and S. center line of the NE 1/4 of
sec. 31.

Ascend 260 ft. over broken S. slope, through heavy timber
and dense undergrowth.

18.20

Spur ridge, bears N. 80° E. and S. 80° W.; desc. 10 ft.
over NW. slope.

19.97

Point for the NE 1/16 sec. cor. of sec. 31, at intersec-
tion with the E. and W. center line of the NE 1/4.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24
ins. in the ground, with aluminum cap mkd.

NE 1/16 S 31
1982

from which

A cedar, 9 ins. diam., bears N. 57 1/2° E., 19 1/2 lks.
dist., mkd. NE 1/16 S31 BT.

A hemlock, 8 ins. diam., bears S. 19° W., 43 lks.
dist., mkd. NE 1/16 S31 BT.

Descend 4]5 ft. over NW. slope, through logged area.