

County Surveyor's Record, Douglas County, Oregon

17094

Subdivision of Sec. 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS					
19.51	<p>The SW 1/16 sec. cor. of sec. 31.</p> <p>Ascend 285 ft. over broken SE. slope.</p>				
39.20	<p>Spur ridge, bears N. and S.; desc. 35 ft. over W. slope.</p>				
43.34	<p>Point for the S 1/16 sec. cor. of sec. 31 only, on the E. bdy. of T. 29 S., R. 10 W.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 1/16</td></tr> <tr><td style="border-right: 1px solid black; padding-right: 5px;">S 31</td></tr> <tr><td style="padding: 0 5px;">1979</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 34 ins. diam., bears N. 8 1/2° E., 34 1/2 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 24 ins. diam., bears S. 25 3/4° E., 21 lks. dist., mkd. S 1/16 S31 BT.</p> <p>From this point, the cor. of Tps. 29 S., Rs. 9 and 10 W., bears S. 0° 45' E., 18.00 chs. dist., described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 29 S., R. 10 W., executed concurrently under these same groups and Group No. 1067.</p>	S 1/16	S 31	1979	
S 1/16					
S 31					
1979					
	<p>From the center W 1/16 sec. cor. of sec. 31.</p> <p>N. 0° 51' W., on the N. and S. center line of the NW 1/4 of sec. 31.</p> <p>Ascend 40 ft. over SE. slope, through moderate timber and undergrowth.</p>				
5.45	<p>Spur ridge, bears N. 70° E. and S. 70° W.; desc. 120 ft. over broken N. slope.</p>				
20.03	<p>Point for the NW 1/16 sec. cor. of sec. 31, at intersection with the E. and W. center line of the NW 1/4.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td style="padding-right: 20px;">NW 1/16</td><td>S 31</td></tr> <tr><td colspan="2">1982</td></tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 24 ins. diam., bears N. 32 3/4° E., 21 lks. dist., mkd. NW 1/16 S31 BT.</p> <p style="margin-left: 40px;">A fir, 22 ins. diam., bears S. 85 3/4° W., 14 lks. dist., mkd. NW 1/16 S31 BT.</p> <p>Descend 55 ft. over broken N. slope.</p>	NW 1/16	S 31	1982	
NW 1/16	S 31				
1982					
21.80	<p>Creek, 1 lk. wide, course N. 60° W.; asc. 55 ft. over SW. slope.</p>				
26.40	<p>Top of ascent, slopes NW.; desc. 190 ft. over broken NE. slope.</p>				
28.35	<p>Gravelled road, 20 lks. wide, bears E. and W.</p>				