

County Surveyor's Record, Douglas County, Oregon

17095

Subdivision of Sec. 31,
T. 29 S., R. 9 W., Willamette Meridian, Oregon

CHAINS					
40.11	The W 1/16 sec. cor. of secs. 30 and 31.				
	<p>From the center N 1/16 sec. cor. of sec. 31.</p> <p>S. 89° 51' W., on the E. and W. center line of the NW 1/4 of sec. 31.</p> <p>Ascend 5 ft. over N. slope, through moderate timber and undergrowth.</p>				
0.50	Top of ascent, slopes NW.; desc. 210 ft. over broken N. slope.				
17.75	Creek, 1 lk. wide, course N. 40° W.; asc. 40 ft. over N. slope.				
19.75	The NW 1/16 sec. cor. of sec. 31.				
	Ascend 10 ft. over N. slope.				
21.25	Spur, slopes N. 30° W.; desc. 40 ft. over SW. slope.				
23.20	Ravine, drains N. 20° W.; asc. 40 ft. over broken NE. slope.				
28.65	Top of ascent, slopes NW.; desc. 145 ft. over broken W. slope.				
43.68	<p>Point for the N 1/16 sec. cor. of sec. 31 only, on the E. bdy. of T. 29 S., R. 10 W.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 10px; height: 15px;"></td> <td style="padding: 0 5px;">N 1/16</td> </tr> <tr> <td style="border-left: 1px solid black; border-right: 1px solid black; width: 10px; height: 15px;"></td> <td style="padding: 0 5px;">S 31</td> </tr> </table> <p>1979</p> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 10 ins. diam., bears N. 41 1/2° E., 20 1/2 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A hemlock, 20 ins. diam., bears S. 85° E., 8 lks. dist., mkd. N 1/16 S31 BT.</p> <p>From this point, the 1/4 sec. cor. of sec. 36 only, on the E. bdy. of T. 29 S., R. 10 W., bears S. 0° 59' E., 18.095 chs. dist., described in the field notes of the dependent resurvey of a portion of the E. bdy. of T. 29 S., R. 10 W., executed concurrently under these same groups and Group No. 1067.</p>		N 1/16		S 31
	N 1/16				
	S 31				
	<p>Remonumentation of Certain Original Corner Points, T. 29 S., R. 9 W., Willamette Meridian, Oregon</p>				
	<p>The following field notes describe the remonumentation of certain original corner points, township 29 south, range 9 west, Willamette Meridian, Oregon, as provided for in the Special Instructions, Group 1000, Oregon, dated July 20, 1979, "Investigation of Physical Evidence of Corner Positions and Accessories, Followed by Remonumentation of Corner Points, with New Accessories When Needed".</p>				