

County Surveyor's Record, Douglas County, Oregon

17100

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

Beginning at the meander cor. of secs. 3 and 34, on the W. shore of Siltcoos Lake, perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd.

LS 849
T 19 S
S 34
S 3
T 20 S
1974

MC

from which the remains of an original bearing tree

A spruce snag, 16 ins. diam., bears N. 13° W., 11 lks. dist., with scribe marks BT visible on open blaze.

and bearing trees mkd. by Foeste

A fir, 18 ins. diam., bears N. 14° E., 41 lks. dist., with scribe marks T19S R12W S34 MC BT visible on partially healed blaze.

A fir, 13 ins. diam., bears N. 67° W., 32 1/2 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

S. 89° 14' W., bet. secs. 3 and 34, marking the true line.

Ascend slightly over nearly level land, through moderate timber and dense undergrowth.

2.10 Enter swamp, edge bears N. and S.; continue over nearly level swampy ground.

7.50 Leave swamp, edge bears N. and S.; asc. slightly over broken E. slope.

8.765 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 19 S R 12 W
1/4 $\frac{S 34}{S 3}$
T 20 S R 12 W
1982

from which

A spruce, 23 ins. diam., bears N. 77° E., 19 lks. dist., mkd. 1/4 S34 BT.

A spruce, 7 ins. diam., bears S. 47 1/2° W., 18 1/2 lks. dist., mkd. 1/4 S3 BT.

From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. 88° 46' W., 0.555 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 1 in. above ground, with brass cap mkd. LS 849 1/4 S3 1974, from which bearing trees mkd. by Foeste: