

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17101

CHAINS

A hemlock, 16 ins. diam., bears S. 17 1/4° E., 92 1/2 lks. dist., with healed blaze.

A spruce, 22 ins. diam., bears S. 15 1/4° W., 74 1/2 lks. dist., with healed blaze.

Ascend 160 ft. over broken E. slope.

26.885

The remains of an original line tree, a rotted spruce stump, 75 ins. diam., no marks remaining. This now becomes an angle point.

At the angle point

Drive an aluminum rod, 4 ft. long, 5/8 in. diam., 3 1/2 ft. in center of stump, with aluminum cap mkd.

AP
T 19 S R 12 W
S 34
S 3
T 20 S R 13 W
1982

from which

A hemlock, 22 ins. diam., bears S. 19° W., 24 lks. dist., mkd. AP S3 BT.

A cedar, 11 ins. diam., bears N. 28° W., 16 lks. dist., mkd. AP S34 BT.

S. 89° 32' W., beginning new measurement.

Ascend slightly over NE. slope.

1.88

Point for the W 1/16 sec. cor. of secs. 3 and 34.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

W 1/16 S 34
S 3
1982

from which

A spruce, 8 ins. diam., bears S. 47° E., 40 lks. dist., mkd. W 1/16 S3 BT.

A hemlock, 14 ins. diam., bears N. 32° W., 28 1/2 lks. dist., mkd. W 1/16 S34 BT.

From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. 89° 07' W., 0.785 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. LS 849 S3 W 1/16 1974, from which bearing trees mkd. by Foeste:

A hemlock, 12 ins. diam., bears S. 77 1/4° E., 30 lks. dist., with scribe marks W 1/16 S3 BT visible on partially healed blaze.

A spruce, 17 ins. diam., bears S. 64 1/4° W., 31 lks. dist., with healed blaze.