

County Surveyor's Record, Douglas County, Oregon

17102

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
21.88	<p>Ascend 120 ft. over broken E. slope.</p> <p>The cor. of secs. 33 and 34 only, perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <p>LS 849</p> <p>T 19 S R 12 W</p> <p>S 33 S 34</p> <p>T 20 S R 12 W</p> <p>S 3</p> <p>1974</p> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A sawed spruce stump, 50 ins. diam., bears N. 70° E., 50 lks. dist., with scribe mark S visible on opened blaze.</p> <p style="margin-left: 40px;">A rotted spruce stump, 45 ins. diam., bears S. 46° E., 80 lks. dist., no marks visible. (Record, S. 50° E.).</p> <p style="margin-left: 40px;">A root hole, bears S. 82° W., 46 lks. dist.</p> <p style="margin-left: 40px;">A rotted hemlock stump, 40 ins. diam., bears N. 51° W., 78 lks. dist., no marks visible.</p> <p>and bearing trees mkd. by Foeste</p> <p style="margin-left: 40px;">A spruce, 28 ins. diam., bears N. 45 3/4° E., 24 lks. dist., with scribe marks T19S R12W. S34 BT visible on open blaze.</p> <p style="margin-left: 40px;">A spruce, 25 ins. diam., bears N. 4 3/4° W., 40 lks. dist., with healed blaze.</p> <p>Land, rolling. Soil, snady loam. Timber, fir, spruce, hemlock, cedar, and chinquapin; undergrowth, salal, huckleberry, vine maple, young timber, Oregon grape, and rhododendron.</p>
1.00	<p>West, on record bearing bet. secs. 3 and 33.</p> <p>Ascend slightly over gentle NE. slope, through moderate timber and undergrowth.</p> <p>The original closing cor. of secs. 3 and 4, hereinafter described.</p> <p>Thence bet. secs. 4 and 33.</p> <p>Ascend slightly over gentle E. slope.</p>
8.60	<p>Top of ascent, slopes N.; desc. 150 ft. over broken NW. slope.</p>
20.80	<p>Point for the E 1/16 sec. cor. of sec. 4 only.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center; margin-top: 10px;"> <p>E 1/16 S 4</p> <p>1982</p> </div>