

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17103

CHAINS

from which

A spruce, 15 ins. diam., bears S. 64 1/2° E., 21
lks. dist., mkd. E 1/16 S4 BT.

A cedar, 26 ins. diam., bears S. 38° W., 50
lks. dist., mkd. E 1/16 S4 BT.

Descend 40 ft. over broken NW. slope.

25.60 E. shore of Erhart Lake, bears N. and S.; continue across
lake.

28.90 W. shore of Erhart Lake, bears N. 30° E. and S. 30° W.;
asc. 55 ft. over broken E. slope.

29.80 U.S. Highway No. 101, asphalt surface, 45 lks. wide,
bears N. 30° E. and S. 30° W.

32.00 Spur ridge, bears N. 45° E. and S. 45° W.; desc. 70 ft.
over broken W. slope.

35.15 Asphalt surfaced road, 35 lks. wide, bears N. 35° E. and
S. 35° W.

40.45 Point for the 1/4 sec. cor. of sec. 33 only, T. 19 S., R.
12 W., at record distance; there is no remaining evidence
of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 23
ins. in the ground, with aluminum cap mkd.

T 19 S R 12 W
 1/4 S 33
T 20 S R 12 W
 1981

from which

A cedar, 7 ins. diam., bears N. 61 1/2° E., 37 1/2
lks. dist., mkd. 1/4 S33 BT.

A pine, 13 ins. diam., bears N. 58 1/2° W., 16 1/2
lks. dist., mkd. 1/4 S33 BT.

Descend slightly over W. slope.

40.80 Point for the 1/4 sec. cor. of sec. 4 only.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24
ins. in the ground, with aluminum cap mkd.

T 19 S R 12 W
 1/4 S 4
T 20 S R 12 W
 1981

from which

A fir, 8 ins. diam., bears S. 17° W., 13 lks.
dist., mkd. X BT.

A pine, 10 ins. diam., bears S. 83° W., 24
lks. dist., mkd. 1/4 S4 BT.

Descend 25 ft. over broken W. slope.

60.80 Point for the W 1/16 sec. cor. of sec. 4 only.