

County Surveyor's Record, Douglas County, Oregon

17104

17104

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} \overline{W\ 1/16} \\ S\ 4 \\ 1982 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">A fir, 18 ins. diam., bears S. 7° E., 54 1/2 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A fir, 25 ins. diam., bears S. 81° W., 42 lks. dist., mkd. W 1/16 S4 BT.</p> <p>Descend 65 ft. over broken W. slope.</p>
66.60	Enter rolling sand dunes with scattering timber and undergrowth.
80.80	<p>Point for the cor. of secs. 4, 5, 32, and 33, at record distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;"> $\begin{array}{c} T\ 19\ S\ R\ 12\ W \\ \hline S\ 32\ \ S\ 33 \\ \hline S\ 5\ \ S\ 4 \\ T\ 20\ S \\ 1982 \end{array}$ </p> <p>from which</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears N. 37° E., 12 lks. dist., mkd. T19S R12W S33 BT.</p> <p style="padding-left: 40px;">A pine, 5 ins. diam., bears S. 65 1/2° E., 13 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">A pine, 7 ins. diam., bears S. 21° W., 34 1/2 lks. dist., mkd. T20S R12W S5 BT.</p> <p style="padding-left: 40px;">A pine, 4 ins. diam., bears N. 79° W., 8 lks. dist., mkd. X BT.</p> <p>Land, rolling. Soil, sand and sandy loam. Timber, spruce, fir, pine, hemlock, cedar, and chinquapin; undergrowth, salal, huckleberry, Scotch broom, rhododendron, young timber, and blackberry.</p>
	<p>West, on record bearing bet. secs. 5 and 32.</p> <p>Descend slightly over rolling sand dunes, through scattering timber and undergrowth.</p>
17.00	Leave timber and undergrowth, edge bears N. and S.; enter open rolling sand dunes.
20.60	<p>Point selected for the witness point on line bet. secs. 5 and 32.</p> <p>Set an aluminum rod, 4 ft. long, 5/8 in. diam., 3 1/2 ft. in ground, in concrete, with aluminum cap mkd.</p>