

County Surveyor's Record, Douglas County, Oregon

17105

Dependent Resurvey, Portion of North Boundary,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	W P T 19 S R 12 W S 32 S 5 T 20 S 1982
	from which A spruce, 10 ins. diam., bears N. 89° E., 392 lks. dist., mkd. X BT. A spruce, 6 ins. diam., bears S. 73° E., 383 lks. dist., mkd. X BT.
22.00	Enter tidal marsh, edge bears N. and S.; continue over nearly level ground.
25.50	Point for the meander cor. of secs. 5 and 32, on the left bank of the Siltcoos River, at record distance; there is no remaining evidence of the original corner, no permanent monument established.
34.92	Point for the meander cor. of secs. 5 and 32, on the right bank of the Siltcoos River, at record distance; there is no remaining evidence of the original corner, no permanent monument established.
40.00	Point for the meander cor. of the shore of the Pacific Ocean, and the 1/4 sec. cor. of secs. 5 and 32, at record distance; there is no remaining evidence of the original corner; impractical to establish a permanent monument.
43.00	Mean high tide and shore of the Pacific Ocean, bears N. 10° E. and S. 10° W.
Dependent Resurvey of a Portion of the Subdivisional Lines, T. 20 S., R. 12 W., Willamette Meridian, Oregon	
(Restoring the survey executed by Harvey Gordon in 1857-58 and the survey by William H. Byars in 1902-05)	
From the point for the cor. of secs. 2, 3, 10, and 11 (located in Siltcoos Lake), at proportionate position, no permanent monument established.	
From this point, the cor. of secs. 1, 2, 11, and 12, and meander cor. on shore of Siltcoos Lake, perpetuated and recorded by W. C. Corbitt for Crown Zellerbach Corporation, in 1941-43, from original evidence, no longer in existence, subsequently perpetuated and recorded by Robert G. Lecklider, Registered Land Surveyor No. 362, in 1958, bears N. 89° 02' E., 78.84 chs. dist., monumented with an iron pipe, 2 ins. diam., firmly set, projecting 1 in. above ground, from which the remains of bearing trees and a bearing object mkd. by Lecklider:	
A powerpole, 10 ins. diam., bears N. 24° E., 40 lks. dist., with scribe marks S1 RE 4079 BP visible.	
A spruce snag, 7 ins. diam., bears S. 41° E., 60 lks. dist., with scribe marks 12 E4 visible on open blaze.	