

# County Surveyor's Record, Douglas County, Oregon

17106

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

A sawed spruce stump, 18 ins. diam., bears S. 5° W., 105 1/2 lks. dist., with scribe marks 79 BT visible on open double blaze.

A spruce, 55 ins. diam., bears N. 86° W., 200 lks. dist., with incorrect scribe marks S11 RE 4079 visible on opened blaze.

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 20 S	R 12 W	
S 2	S 1	MC
S 11	S 12	
1982		

from which new bearing trees

A spruce, 8 ins. diam., bears S. 7° E., 91 lks. dist., mkd. T20S R12W S12 BT.

A spruce, 7 1/2 ins. diam., bears S. 4° W., 77 1/2 lks. dist., mkd. T20S R12W S11 BT.

Deposit iron pipe alongside aluminum post.

This control line was fully retraced and careful search was made for evidence of intervening corners, none of which was recovered.

From this same point, the middle meander cor. of secs. 10 and 11, on Siltcoos Lake, perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. 2° 28' E., 8.99 chs. dist., monumented with an iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

LS 849		
T 20 S	R 12 W	
S 10	S 11	
MC		
1974		

from which the remains of an original bearing tree

A sawed fir stump, 38 ins. diam., bears N. 20 1/2° W., 42 1/2 lks. dist., (40 lks. to face), no marks visible on open rotted blaze. (Record, N. 24° W., 40 lks.)

and a new bearing tree

A spruce, 15 ins. diam., bears N. 64° W., 79 lks. dist., mkd. T20S R12W S10 MC BT.

No suitable tree available in sec. 11.

This control line was fully retraced and careful search was made for the intervening meander corner, which was not recovered.

North, on record bearing bet. secs. 2 and 3, marking the true line.

Across Siltcoos Lake.