

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17107

CHAINS	
9.85	Point for the most southerly meander cor. of secs. 2 and 3 on Siltcoos Lake, at record distance; there is no remaining evidence of the original corner, no permanent monument established.
10.00	Shore of Siltcoos Lake, bears N. 60° W. and S. 60° E.; enter heavy timber and dense undergrowth.
16.78	Point for the middle meander cor. of secs. 2 and 3, on Siltcoos Lake at record distance; there is no remaining evidence of the original corner. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} \text{MC} \\ \hline \text{S } 3 \downarrow \text{S } 2 \\ \text{T } 20 \text{ S } \quad \text{R } 12 \text{ W} \\ 1982 \end{array}$
	from which A spruce, 21 ins. diam., bears S. 54 1/2° E., 31 lks. dist., mkd. T20S R12W S2 MC BT. A spruce, 37 ins. diam., bears S. 61 1/2° W., 85 lks. dist., mkd. T20S R12W S3 MC BT.
	Descend slightly over nearly level land.
18.36	Shore of Siltcoos Lake, bears E. and W. curving to NW.; thence across lake.
52.70	South shore of Booth Island, bears NW. and SE., and point for the meander cor. of secs. 2 and 3, at record distance; there is no remaining evidence of the original corner, no permanent monument established. Thence across island, through dense brush.
61.00	North shore of Booth Island, bears NW. and SE., and point for the terminal meander cor. of secs. 2 and 3, at record distance; there is no remaining evidence of the original corner, no permanent monument established.
	From the point for the cor. of secs. 2, 3, 10, and 11. S. 87° 46' W., bet. secs. 3 and 10. Across Siltcoos Lake.
11.70	Shore of Siltcoos Lake, bears N. and S., enter moderate timber and dense undergrowth; asc. 5 ft. over nearly level land.
11.88	The most easterly meander cor. of secs. 3 and 10 on shore of Siltcoos Lake, perpetuated and recorded by W. G. Corbitt, for Crown Zellerbach Corporation, in 1941-43, subsequently perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, with brass cap mkd.
	$\begin{array}{c} \text{LS } 849 \\ \text{T } 20 \text{ S} \\ \text{S } 3 \downarrow \text{S } 10 \\ \text{R } 12 \text{ W} \\ 1974 \end{array} \quad \text{MC}$
	<i>FOOK 34 R. Ward 4/95 M122-9</i>