

# County Surveyor's Record, Douglas County, Oregon

17109

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

**CHAINS**

S. 87° 07' W., beginning new measurement.

Descend slightly over nearly level land.

0.15 Shore of Siltcoos Lake, bears N. 10° E. and S. 10° W.;  
continue across lake.

9.60 Shore of Siltcoos Lake, bears N. and S.; enter moderate  
timber and dense undergrowth; asc. slightly over nearly  
level swampy land.

11.00 The most westerly meander cor. of secs. 3 and 10 on shore  
of Siltcoos Lake, monumented with the remains of the  
original corner tree, a rotted fir stump, 72 ins. diam.,  
no marks visible, from which the remains of an original  
bearing tree:

A rotted fir stump, 44 ins. diam., bears N. 18° W.,  
78 lks. dist., no marks visible. (Record,  
N. 12° W., 60 lks.)

At the corner point

Drive an aluminum rod, 4 ft. long, 5/8 in. diam., 3 1/2 ft.  
in center of stump, with aluminum cap mkd.

T 20 S  
S 3 / MC  
S 10 /  
R 12 W  
1982

*FDOK  
BY R. Ward  
4/2 1122-4*

from which new bearing trees

A spruce, 12 ins. diam., bears S. 31 1/2° W., 17  
lks. dist., mkd. T20S R12W S10 MC BT.

A spruce, 10 ins. diam., bears N. 71 1/2° W., 14  
lks. dist., mkd. T20S R12W S3 MC BT.

N. 88° 48' W., beginning new measurement.

Continue over nearly level swampy land.

10.96 The 1/4 sec. cor. of secs. 3 and 10, perpetuated and  
recorded by W. G. Corbitt, for Crown Zellerbach Corpora-  
tion, in 1941-43, from original evidence no longer in  
existence, subsequently perpetuated and recorded by John  
M. Powell, for the County Surveyor, in 1971, and by Karl  
F. Foeste, Registered Land Surveyor, No. 849, in 1974,  
monumented with an iron post, 2 ins. diam., firmly set,  
projecting 5 ins. above ground, with brass cap mkd.

LS 849  
1/4 S 3 /  
S 10 /  
1974

*FDOK  
BY R. Ward  
4/2 1122-4*

from which the remains of the bearing trees mkd. by  
Powell

A sawed hemlock stump, 30 ins. diam., bears  
N. 16° E., 57 1/2 lks. dist., no marks visible.

An alder snag, 7 ins. diam., bears N. 37 1/2° E.,  
14 lks. dist., with scribe marks 1/4 S3 CS BT  
visible on open blaze.