

County Surveyor's Record, Douglas County, Oregon

17111

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	N. 0° 16' W., bet. secs. 3 and 4.
	Ascend slightly over SE. slope, through moderate timber and dense undergrowth.
4.00	Top of ascent, slopes NE.; desc. 160 ft. over N. slope.
13.25	Gravelled road, 30 lks. wide, bears N. 40° W. and S. 40° E.
16.50	Creek, 3 lks. wide, bears N. 40° W. and S. 40° E.
16.50	Creek, 3 lks. wide, course N. 50° E.; asc. 170 ft. over broken SE. slope.
39.94	The 1/4 sec. cor. of secs. 3 and 4, perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd.
	LS 849 1/4 S 4 S 3 1974
	from which the remains of an original bearing tree
	A rotted hemlock stump, 12 ins. diam., bears S. 10° E., 14 lks. dist., with rotted blaze, no marks visible.
	and bearing trees mkd. by Foeste
	A hemlock, 13 ins. diam., bears S. 56° E., 42 1/2 lks. dist., with healed blaze.
	A hemlock, 12 ins. diam., bears S. 59 1/2° W., 6 lks. dist., with healed blaze.

	N. 0° 02' W., beginning new measurement.
	Ascend 80 ft. over broken SE. slope.
15.00	Slope changes to SW.
20.075	Point for the N 1/16 sec. cor. of secs. 3 and 4.
	Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.
	N 1/16 S 4 S 3 1982
	from which
	A cedar, 10 ins. diam., bears N. 87 1/4° E., 25 lks. dist., mkd. N 1/16 S3 BT.
	A spruce, 12 ins. diam., bears N. 75° W., 1 1/2 lks. dist., mkd. N 1/16 S4 BT.
	Ascend 100 ft. over broken SW. slope.
36.80	Top of ascent, slopes E.; desc. 50 ft. over NE. slope.
43.46	Intersect the S. bdy. of sec. 33, T. 19 S., R. 12 W., at the original closing cor. of secs. 3 and 4, perpetuated and recorded by Karl F. Foeste, Registered Land Surveyor,