


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17115

CHAINS




from which new bearing trees

A fir, 6 ins. diam., bears S. 12° E., 7 1/2 lks. dist., mkd. T20S R12W S28 MC BT.

A spruce, 7 ins. diam., bears S. 30° W., 12 1/2 lks. dist., mkd T20S R12W S29 MC BT.

From the 1/4 sec. cor. of secs. 20 and 21, perpetuated and recorded by W. G. Corbitt for Crown Zellerbach Corporation, in 1943, subsequently perpetuated and recorded by J. M. Powell for the County Surveyor, in 1971, monumented with an iron pipe, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.



from which the remains of the original bearing trees

A sawed spruce stump, 60 ins. diam., bears N. 21° E., 17 lks. dist., no marks visible. (Record, N. 10° E.)

A sawed fir stump, 48 ins. diam., bears S. 73° W., 8 lks. dist., no marks visible on open blaze. (Record, spruce).

and bearing trees mkd. by Powell

A fir, 15 ins. diam., bears S. 87 1/2° E., 45 lks. dist., with healed blaze.

A spruce, 21 ins. diam., bears S. 59 1/2° W., 31 lks. dist., with healed blaze.

This corner is identical with Angle Point No. 7 of Parcel E.

From this point, a point established by person(s) unknown, bears N. 58° 01' E., 0.565 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above ground.

N. 0° 34' W., bet. secs. 20 and 21.

Ascend 15 ft. over SW. slope, through moderate timber and dense undergrowth.

- | | |
|-------|---|
| .70 | Spur, slopes N. 80° W.; desc. 130 ft. over NE. slope. |
| 3.95 | Ravine, drains N. 70° W.; asc. 170 ft. over SW. slope. |
| 9.85 | Spur, slopes N. 60° W.; desc. 160 ft. over NE. slope. |
| 15.65 | Gravelled road, 25 lks. wide, bears N. 80° E. and S. 80° W. |
| 17.05 | Bottom of descent, slopes W.; asc. 35 ft. over SW. slope. |