

County Surveyor's Record, Douglas County, Oregon

17116

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS																
	<p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td style="padding: 0 5px;">N 1/16</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td style="padding: 0 5px;">S 20</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1981</td> </tr> </table> </div> <p>from which</p> <p style="margin-left: 40px;">A hemlock, 11 ins. diam., bears N. 45 1/2° E., 10 lks. dist., mkd. N 1/16 S21 BT.</p> <p style="margin-left: 40px;">A spruce, 11 ins. diam., bears N. 42 1/4° W., 8 1/2 lks. dist., mkd. N 1/16 S20 BT.</p> <p>Corner is located at top of ascent, slopes SW.</p> <p>Descend 155 ft. over NE. slope.</p>	N 1/16		S 21	S 20		S 21	1981								
N 1/16		S 21														
S 20		S 21														
1981																
28.33	Point for Angle Point 1, Parcel E, hereinafter described.															
29.00	Bottom of descent, slopes W.; asc. 150 ft. over SW. slope.															
37.45	Top of ridge, bears NE. and SW.; desc. 15 ft. over N. slope.															
40.15	<p>The cor. of secs. 16, 17, 20 and 21, perpetuated and recorded by John M. Powell for the County Surveyor, in 1971, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border-collapse: collapse;"> <tr> <td colspan="3" style="padding: 0 5px;">T 20 S</td> </tr> <tr> <td style="padding: 0 5px;">S 17</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 16</td> </tr> <tr> <td style="padding: 0 5px;">S 20</td> <td style="padding: 0 5px;"> </td> <td style="padding: 0 5px;">S 21</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">R 12 W</td> </tr> <tr> <td colspan="3" style="text-align: center; padding: 0 5px;">1971</td> </tr> </table> </div> <p>from which the remains of the original bearing trees</p> <p style="margin-left: 40px;">A fir snag, 18 ins. diam., bears S. 67° E., 70 lks. dist., with scribe marks S21 T20S R12W visible on opened double blaze.</p> <p style="margin-left: 40px;">A root hole, bears S. 45° W., 15 lks. dist., alongside of which is lying a spruce, size indeterminate, no marks visible.</p> <p>and a bearing tree mkd. by Powell</p> <p style="margin-left: 40px;">A fir, 15 ins. diam., bears S. 29° W., 24 lks. dist., with healed blaze.</p> <p>and new bearing trees</p> <p style="margin-left: 40px;">A spruce, 17 ins. diam., bears S. 70 1/2° E., 102 lks. dist., mkd. T20S R12W S21 BT.</p> <p style="margin-left: 40px;">A pine, 20 ins. diam., bears N. 78° W., 80 lks. dist., mkd. T20S R12W S17 BT.</p> <p>Land, mountainous. Soil, sandy loam. Timber, fir, pine, spruce; undergrowth, huckleberry, rhododendron, salal, Scotch broom, thimbleberry.</p>	T 20 S			S 17		S 16	S 20		S 21	R 12 W			1971		
T 20 S																
S 17		S 16														
S 20		S 21														
R 12 W																
1971																

N. 0° 38' W., bet. secs. 16 and 17.