

# County Surveyor's Record, Douglas County, Oregon

17118

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

N 1/16  
S 17 | S 16  
1982

from which

A spruce, 15 ins. diam., bears S. 74 1/2° E., 18 lks. dist., mkd. N 1/16 S16 BT.

A spruce, 15 ins. diam., bears N. 81° W., 18 1/2 lks. dist., mkd N 1/16 S17 BT.

Descend 150 ft. over broken NE. slope.

70.40 Stream, course S. 80° E.; asc. 60 ft. over SW. slope.

79.75 Top of ascent, slopes W.; desc. 75 ft. over N. slope.

80.00 Bottom of descent, slopes N. 80° E.; asc. 15 ft. over SE. slope.

81.88 The cor. of secs. 8, 9, 16, and 17, perpetuated and recorded by W. G. Corbitt, for Crown Zellerbach Corporation, in 1943, monumented with an iron pipe, 2 ins. diam., firmly set, projecting 6 ins. above ground, from which the remains of the original bearing trees:

A sawed spruce stump, 25 ins. diam., bears N. 86° E., 68 lks. dist., with illegible scribe marks visible on open blaze. (Record and to face, 67 lks.)

A sawed spruce stump, 44 ins. diam., bears S. 24° E., 34 lks. dist., no marks visible on opened blaze. (Record, 31 lks.)

A sawed spruce stump, 46 ins. diam., bears S. 70° W., 12 lks. dist., no marks visible on open blaze. (Record, 9 lks.)

A sawed spruce stump, 36 ins. diam., bears N. 2° W., 27 lks. dist., with scribe marks T20 R12E visible on partially opened blaze. (Record, 25 lks.)

At the corner point

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 20 S R 12 W  
S 8 | S 9  
S 17 | S 16  
1982

*FD OK BY  
R. Word  
M 122-4*

from which new bearing trees

A spruce, 14 ins. diam., bears N. 57° E., 34 lks. dist., mkd. T20S R12W S9 BT.

A spruce, 15 ins. diam., bears S. 61° E., 7 lks. dist., mkd. T20S R12W S16 BT.

A hemlock, 10 ins. diam., bears S. 45 1/2° W., 30 lks. dist., mkd. T20S R12W S17 BT.

A fir, 7 ins. diam., bears N. 58° W., 39 lks. dist., mkd T20S R12W S8 BT.

Reset iron pipe alongside aluminum post.