

County Surveyor's Record, Douglas County, Oregon

17123

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

in. above ground, from which bearing trees mkd. by Colling:

A pine, 10 ins. diam., bears S. 51° W., 98 lks. dist., no marks visible on open double blaze.

A pine, 12 ins. diam., bears N. 60 1/2° W., 69 lks. dist., no marks visible on open double blaze.

N. 2° 09' W., beginning new measurement.

Over nearly level land, through moderate timber and undergrowth.

5.90 Leave moderate timber and undergrowth, edge bears N. 70° E. and S. 70° W.; enter rolling sand dunes with scattering timber and undergrowth.

20.615 Point for the N 1/16 sec. cor. of secs. 4 and 5.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.

N 1/16
S 5 | S 4
1982

from which

A pine, 6 ins. diam., bears N. 57° E., 49 lks. dist., mkd. N 1/16 S4 BT.

A pine, 8 ins. diam., bears S. 23 1/2° W., 122 lks. dist., mkd. N 1/16 S5 BT.

Continue over nearly level land.

41.48 The cor. of secs. 4, 5, 32, and 33, on the N. bdy. of the Tp.

Land, rolling.

Soil, sand and sandy loam.

Timber, spruce, fir, pine, hemlock, and cedar; undergrowth, huckleberry, salal, willow, Scotch broom, rhododendron, and beach grass.

From the cor. of secs. 5, 6, 31 and 32, on the S. bdy. of the Tp., monumented with an aluminum post, 2 1/2 ins. diam., firmly set, projecting 5 ins. above ground, with aluminum cap mkd.

T 20 S R 12 W
S 31 | S 32
S 6 | S 5
T 21 S
1981

from which bearing trees mkd. by Goodson, McIntyre, and McMullin

A spruce, 32 ins. diam., bears N. 59° E., 75 1/2 lks. dist., with scribe marks T20S R12W S32 BT visible on open blaze.

A spruce, 22 ins. diam., bears S. 16° E., 54 1/2 lks. dist., with scribe marks T21S R12W S5 BT visible on open blaze.