

County Surveyor's Record, Douglas County, Oregon

17124

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p>A spruce, 19 ins. diam., bears S. 56° W., 37 lks. dist., with scribe marks T21S R12W S6 BT visible on open blaze.</p> <p>A spruce, 17 ins. diam., bears N. 27° W., 17 1/2 lks. dist., with scribe marks T20S R12W S31 BT visible on open blaze.</p> <p>N. 0° 38' W., bet. secs. 31 and 32.</p> <p>Ascend 70 ft. over SW. slope, through moderate timber and dense undergrowth.</p>
8.00	Top of ascent, slopes NW.; desc. 80 ft. over broken NW. slope.
16.00	Bottom of descent, slopes W.; asc. 80 ft. over broken SW. slope.
40.00	<p>Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 20 S R 12 W</p> <p style="margin-left: 100px;">1/4</p> <p style="margin-left: 80px;">S 31 S 32</p> <p style="margin-left: 100px;">1981</p> </div> <p>from which</p> <p>A pine, 15 ins. diam., bears N. 63° E., 9 1/2 lks. dist., mkd. 1/4 S32 BT.</p> <p>A spruce, 12 ins. diam., bears S. 48 3/4° W., 53 lks. dist., mkd. 1/4 S31 BT.</p> <p>Ascend 20 ft. over SW. slope.</p>
41.40	Top of ascent, slopes W.; desc. 120 ft. over broken NW. slope.
59.00	Leave timber and undergrowth, edge bears NE. and SW.; enter rolling sand dunes with scattering timber and undergrowth.
80.00	<p>Point for the cor. of secs. 29, 30, 31, and 32, determined by the method of two point control; there is no remaining evidence of the original corner.</p> <p>Set an aluminum rod, 4 ft. long, 5/8 in. diam., 4 ft. in the ground, in concrete, with aluminum cap mkd.</p> <div style="text-align: center;"> <p>T 20 S R 12 W</p> <p style="margin-left: 100px;">S 30 S 29</p> <p style="margin-left: 80px;">S 31 S 32</p> <p style="margin-left: 100px;">1981</p> </div> <p>from which</p> <p>A pine, 5 ins. diam., bears N. 35 1/2° E., 34 1/2 lks. dist., mkd. X BT.</p> <p>A pine, 5 ins. diam., bears S. 47 3/4° E., 29 lks. dist., mkd. X BT.</p> <p>A pine, 7 ins. diam., bears S. 20 1/4° W., 49 lks. dist., mkd. T20S R12W S31 BT.</p>