

# County Surveyor's Record, Douglas County, Oregon

17125

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">A pine, 8 ins. diam., bears N. 70 1/4° W., 48 lks. dist., mkd. T20S R12W S30 BT. ---</p> <p>Land, rolling hills. Soil, sand and sandy loam. Timber, spruce, fir, pine, hemlock, and cedar; undergrowth, salal, huckleberry, rhododendron, vine maple, young timber, blackberry, Scotch broom, and Oregon grape.</p>
	<p>From the cor. of secs. 28, 29, 32, and 33.</p> <p>S. 89° 16' W., bet. secs. 29 and 32.</p> <p>Descend 120 ft. over broken NW. slope, through moderate timber and dense undergrowth.</p>
5.30	E. edge of swamp, bears N. 10° W. and S. 10° E.; thence across swamp.
12.20	W. edge of swamp, bears N. 10° W. and S. 10° E.; asc. 30 ft. over NE. slope, through moderate timber and dense undergrowth.
18.40	U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears N. 4 1/2° E. and S. 4 1/2° W.
18.805	Intersect the westerly right-of-way of U.S. Highway No. 101.
	Point for Angle Point No. 2 of Parcel A, hereinafter described.
20.215	Point for the E 1/16 sec. cor. of secs. 29 and 32.
	$E \frac{1}{16} \begin{array}{l} S \ 29 \\ S \ 32 \end{array}$ 1981
	<p>from which</p> <p style="padding-left: 40px;">A spruce, 20 ins. diam., bears N. 34 3/4° E., 93 lks. dist., mkd. E 1/16 S29 BT.</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears S. 7° E., 40 lks. dist., mkd. E 1/16 S32 BT.</p> <p>From this point, a point established by person(s) unknown, bears N. 35° 45' E., 0.855 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, projecting 1 in. above ground.</p> <p>Ascend 140 ft. over NE. slope.</p>
28.00	Top of ascent, slopes N.; desc. 65 ft. over NW. slope, also enter rolling sand dunes with scattering timber and undergrowth.
40.43	Point for the 1/4 sec. cor. of secs. 29 and 32, at proportionate distance; there is no remaining evidence of the original corner.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T 20 S R 12 W 1/4 <math>\begin{array}{l} S \ 29 \\ S \ 32 \end{array}</math> 1981</p>