


County Surveyor's Record, Douglas County, Oregon

17127

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS



No suitable trees available.

Set a steel fence post alongside aluminum rod.

Corner is located on S. edge of tidal flat, bears N. 20° E. and S. 20° W.

Continue across tidal flat.

75.50 Tahkenitch Creek, 100 lks. wide, course S. 30° W.; continue across tidal flat.

80.00 True point for the cor. of secs. 19, 20, 29, and 30, determined by the method of two point control. This position was originally located in Tahkenitch Creek and was not monumented. No permanent monument established.

Land, nearly level.

Soil, sand.


Timber, pine, and chinquapin; undergrowth, Scotch broom, young timber, willow, and beach grass.

From the cor. of secs. 20, 21, 28, and 29, perpetuated and recorded by W. G. Corbitt for Crown Zellerbach Corporation, in 1941-43, determined at record bearing and distance from the remains of an original bearing tree:

A rotted spruce stump, 36 ins. diam., bears N. 78° E., 9 lks. dist., no marks visible on open rotted blaze. Found Corbitt's 2 in. diam. iron pipe, mostly rusted away, in top of stump.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.



from which the remains of a bearing tree mkd. by person(s) unknown, found and described by Corbitt in 1941

A rotted spruce stump, 44 ins. diam., bears N. 50° W., 37 lks. dist., with axe marks visible on an opened blaze.

and new bearing trees

A spruce, 15 ins. diam., bears N. 36° E., 102 lks. dist., mkd. T20S R12W S21 BT.

A fir, 17 ins. diam., bears S. 33 3/4° E., 93 1/2 lks. dist., mkd. T20S R12W S28 BT.

A spruce, 15 ins. diam., bears S. 74° W., 69 lks. dist., mkd. T20S R12W S29 BT.

A fir, 16 ins. diam., bears N. 50° W., 48 1/2 lks. dist., mkd. T20S R12W S20 BT.