

County Surveyor's Record, Douglas County, Oregon

17128

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS

S. 88° 06' W., bet. secs. 20 and 29.

Descend 190 ft. over SW. slope, through scattering timber and dense undergrowth.

7.15 Ravine, drains S. 34° W.; asc. 80 ft. over SE. slope.

17.70 Spur, slopes S. 10° E.; desc. 170 ft. over NW. slope.

31.35 Bottom of descent, slopes N.; asc. 20 ft. over SE. slope.

33.30 Top of ascent, slopes SW.; desc. 120 ft. over broken W. slope.

37.55 U.S. Highway No. 101, asphalt surface, 60 lks. wide, bears N. 10° W. and S., in curve.

38.00 Enter swamp, edge bears N. and S.

40.62 Point for the 1/4 sec. cor. of secs. 20 and 29, at proportionate distance; there is no remaining evidence of the original corner.

Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.

T 20 S R 12 W
1/4 S 20
S 29
1982

from which

A spruce, 15 ins. diam., bears N. 18 1/2° E., 306 lks. dist., mkd. 1/4 S20 BT.

A spruce, 8 ins. diam., bears S. 13 1/4° E., 52 lks. dist., mkd. 1/4 S29 BT.

Continue across swamp.

42.30 Leave swamp, edge bears N. and S.; enter scattering timber and dense undergrowth.

44.80 Tahkenitch Creek, 100 lks. wide, course N.; asc. slightly over NE. slope.

46.34 Point for the meander cor. of secs. 20 and 29, on the right bank of Tahkenitch Creek, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

MC T 20 S
S 20
S 29
R 12 W
1982

from which

A fir, 20 ins. diam., bears N. 66 1/4° E., 52 1/2 lks. dist., mkd. T20S R12W S20 MC BT.

A fir, 40 ins. diam., bears S. 25 1/2° E., 57 1/2 lks. dist., mkd. T20S R12W S29 MC BT.