


County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17131

CHAINS

T 20 S R 12 W



from which

A pine, 7 ins. diam., bears N. 26 1/2° E., 22 1/2 lks. dist., mkd. X BT.

Set a steel fence post alongside iron post.


Corner is located on E. edge of swampy inlet of Tahkenitch Creek and on W. edge of scattering trees and dense undergrowth.

Ascend slightly over open grassy dunes.

40.00

Point for the 1/4 sec. cor. of secs. 19 and 20, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in concrete, with brass cap mkd.



No suitable trees available.


Set a steel fence post alongside iron post.

Continue across open dunes.

60.00

Point for the N 1/16 sec. cor. of secs. 19 and 20.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, in concrete, with brass cap mkd.




No suitable trees available.

Continue across open dunes.

80.00

Point for the cor. of sections 17, 19, and 20, and meander cor. on the shore of the Pacific Ocean, determined by the method of two point control; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, in concrete, with brass cap mkd.



No suitable trees available.