

County Surveyor's Record, Douglas County, Oregon

17132

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p style="text-align: center;">Set wooden post, 8 ft. long, 4 ins. diam., alongside iron post.</p> <p>Corner is located on E. slope of 10 ft. high sea wall, 3 chs. E. of mean high tide and shore of Pacific Ocean, which bears N. 10° E. and S. 10° W.</p> <p>Land, tidal flats and rolling sand dunes. Soil, sand. Timber, pine; undergrowth, grasses.</p>
	<p>From the cor. of secs. 16, 17, 20, and 21.</p> <p>S. 88° 04' W., bet. secs. 17 and 20.</p> <p>Descend 125 ft. over broken SW. slope, through scattering timber and dense undergrowth.</p>
14.30	Bottom of descent, slopes NW.; asc. 25 ft. over NE. slope.
15.90	Ridge, bears N. and S.; desc. 50 ft. over SW. slope.
18.50	U.S. Highway No. 101, asphalt surface, 60 lks. wide, bears NW. and SE., in curve.
19.81	<p>Point selected for the witness cor. to the E 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> $\begin{array}{c} \text{WC} \\ \leftarrow \begin{array}{l} \text{S } 17 \\ \text{S } 20 \end{array} \\ \text{E } 1/16 \\ \text{1982} \end{array}$ </div> <p>from which</p> <p style="margin-left: 40px;">A fir, 14 1/2 ins. diam., bears S. 33 3/4° E., 24 1/2 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">A fir, 8 ins. diam., bears N. 32 1/4° W., 42 lks. dist., mkd. X BT.</p> <p style="margin-left: 40px;">Set a steel fence post alongside iron post.</p> <p>Descend 20 ft. over W. slope.</p>
19.90	E. edge of lake, bears N. 40° W. and S. 25° E.; thence across lake.
20.31	True point for the E 1/16 sec. cor. of secs. 17 and 20 is located in a lake, where it is impracticable to establish a permanent monument.
22.85	W. edge of lake, bears N. 60° W. and S. 60° E.; asc. 80 ft. over broken SE. slope, through moderate timber and dense brush.
33.75	Top of ascent, slopes N.; desc. 60 ft. over NW. slope.
37.20	Enter open, rolling sand dunes, edge bears N. and S.
40.62	Point for the 1/4 sec. cor. of secs. 17 and 20, at proportionate distance; there is no remaining evidence of the original corner.