

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17133

CHAINS	
	<p>Set an aluminum rod, 18 ft. long, 5/8 in. diam., 17 1/2 ft. in the ground, in concrete, with aluminum cap mkd.</p> <p style="text-align: center;">T 20 S R 12 W 1/4 $\frac{S 17}{S 20}$ 1982</p> <p>from which</p> <p style="padding-left: 40px;">A spruce, 13 ins. diam., bears N. 60 1/2° E., 396 lks. dist., mkd. 1/4 S17 BT.</p> <p style="padding-left: 40px;">A spruce, 30 ins. diam., bears S. 37° E., 485 lks. dist., mkd. 1/4 S20 BT.</p> <p style="padding-left: 40px;">Set a steel fence post alongside aluminum rod.</p> <p>Descend 95 ft. over rolling sand dunes.</p>
60.93	<p>Point for the W 1/16 sec. cor. of secs. 17 and 20.</p> <p>Set an aluminum post, 28 ins. long., 2 1/2 ins. diam., 23 ins. in the ground, in concrete, with aluminum cap mkd.</p> <p style="text-align: center;">W 1/16 $\frac{S 17}{S 20}$ 1982</p> <p style="padding-left: 40px;">No suitable trees available.</p> <p style="padding-left: 40px;">Set a steel fence post alongside aluminum post.</p> <p>Descend slightly over rolling sand dunes.</p>
81.24	<p>the cor. of secs. 17, 19, and 20, and meander cor. on the shore of the Pacific Ocean.</p> <p>Land, rolling. Soil, sand and sandy loam. Timber, spruce, fir, pine; undergrowth, salal, Scotch broom, huckleberry, rhododendron, and beach grasses.</p>
2.00	<p>From the cor. of secs. 8, 9, 16, and 17.</p> <p>West, on record bearing bet. secs. 8 and 17.</p> <p>Descend 70 ft. over NW. slope, through moderate timber and dense undergrowth.</p>
.50	<p>Ravine, drains N. 40° E.; asc. 60 ft. over NE. slope.</p> <p>Top of ascent, slopes N.; desc. 100 ft. over broken NW. slope.</p>
20.00	<p>Point for the E 1/16 sec. cor. of secs. 8 and 17, is located in the north-bound lane of U.S. Highway No. 101.</p> <p>Drive a "PK" nail flush with the surface of the highway.</p> <p>from which</p> <p style="padding-left: 40px;">An aluminum post, 28 ins. long, 2 1/2 ins. diam., set 24 ins. in the ground, for a reference monument, bears S. 45° E., 76 lks. dist., with aluminum cap mkd. E 1/16 S17 50 FT TO COR 1982 and an arrow pointing to the corner.</p>