

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

17137

CHAINS

No suitable trees available.

Set a steel fence post alongside aluminum rod.

Descend slightly over sand dunes.

15.00

Mean high tide and shore of the Pacific Ocean, bears N. 10° E. and S. $6\frac{1}{2}^{\circ}$ W.; true point for the meander cor. of secs. 19 and 30, on the shore of the Pacific Ocean, at record distance; there is no remaining evidence of the original corner. This point is located at edge of beach, where it is impracticable to establish a permanent monument.

Land, nearly level.
Soil, sand.
Vegetation, beach grass.

Subdivision of Section 3,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

From the $\frac{1}{4}$ sec. cor. of secs. 3 and 10.

N. $0^{\circ} 16'$ E., on the N. and S. center line of sec. 3.

Descend slightly over nearly level swampy ground, through moderate timber and undergrowth.

14.00

Bottom of descent, slopes SE.; asc. 120 ft. over SE. slope.

14.55

Gravelled road, 20 lks. wide, bears E. and W.

23.40

Gravelled road, 20 lks. wide, bears N. 60° E. and S. 60° W.

40.80

Point for the center $\frac{1}{4}$ sec. cor. of sec. 3, at intersection with the E. and W. center line.

Set an aluminum post, 28 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with aluminum cap mkd.

T 20 S R 12 W
C $\frac{1}{4}$ S 3
1982

from which

A spruce, 26 ins. diam., bears N. 69° E., 13 lks. dist., mkd. C $\frac{1}{4}$ S3 BT.

A cedar, 22 ins. diam., bears N. 19° W., 18 lks. dist., mkd. C $\frac{1}{4}$ S3 BT.

From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. $51^{\circ} 13'$ W., 0.345 chs. dist., monumented with an iron post, 2 ins. diam., firmly set, projecting 2 ins. above ground, with brass cap mkd. LS 849 C $\frac{1}{4}$ S3 1974, from which the bearing trees mkd. by Foeste

A spruce, 22 ins. diam., bears N. $50\frac{1}{2}^{\circ}$ E., $54\frac{1}{2}$ lks. dist., with partially healed blaze, no marks visible.

A spruce, 25 ins. diam., bears S. $87\frac{1}{2}^{\circ}$ W., $53\frac{1}{2}$ lks. dist., with partially healed blaze, no marks visible.