

County Surveyor's Record, Douglas County, Oregon

17138

Subdivision of Sec. 3,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	Ascend 25 ft. over SE. slope.
47.00	Top of ascent, slopes E.; desc, 140 ft. over NW. slope.
60.965	Point for the center N 1/16 sec. cor. of sec. 3.
	Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 25 ins. in the ground, with aluminum cap mkd.
	$\begin{array}{c} C \\ N\ 1/16 \quad \quad S\ 3 \\ C \\ 1982 \end{array}$
	from which
	A spruce, 12 ins. diam., bears N. 24 1/2° E., 14 1/2 lks. dist., mkd. CN 1/16 S3 BT.
	A spruce, 13 ins. diam., bears S. 70° W., 10 lks. dist., mkd. CN 1/16 S3 BT.
	From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. 73° 59' W., 0.43 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. LS 849 CN 1/16 S3 1974, from which bearing trees mkd. by Foeste:
	A spruce, 22 ins. diam., bears S. 54 1/2° W., 25 lks. dist., with scribe marks N S3 BT visible on partially healed blaze.
	A spruce, 26 ins. diam., bears N. 8 3/4° W., 24 1/2 lks. dist., with partially healed blaze, no marks visible.
	Descend 35 ft. over NW. slope.
63.30	Ravine, drains N. 60° E.; asc. 40 ft. over S. slope.
66.20	Top of ascent, slopes E.; desc. 50 ft. over N. slope.
68.30	Enter swamp, edge bears E. and W.; continue over nearly level land.
69.805	Intersect the adjusted meanders of Siltcoos Lake; point for the special meander cor. on the N. and S. center line of sec. 3. No permanent monument established.
72.60	Leave swamp, edge bears E. and W.; asc. 60 ft. over S. slope.
73.405	Intersect the adjusted meanders of Siltcoos Lake; point for the special meander cor. on the N. and S. center line of sec. 3. No permanent monument established.
83.00	Top of ascent, slopes E.; desc. 55 ft. over N. slope.
84.00	Ravine, drains E.; asc. 20 ft. over SE. slope.
84.46	The 1/4 sec. cor. of secs. 3 and 34, on the N. bdy, of the Tp.
	From the 1/4 sec. cor. of secs. 3 and 4, N. 89° 44' E., on a weighted mean bearing on the E. and W. center line of sec. 3.