

County Surveyor's Record, Douglas County, Oregon

17140

Subdivision of Sec. 3,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	NW 1/16 S 3 1982
	<p>from which</p> <p style="padding-left: 40px;">A spruce, 16 ins. diam., bears N. 4 1/2° E., 21 lks. dist., mkd. NW 1/16 S3 BT.</p> <p style="padding-left: 40px;">A hemlock, 12 ins. diam., bears N. 77° W., 19 lks. dist., mkd. NW 1/16 S3 BT.</p> <p>From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears S. 84° 21' W., 0.66 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. LS 849 NW 1/16 S3 1974, from which bearing trees mkd. by Foeste:</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears S. 85° E., 35 lks. dist., with scribe marks NW 1/16 S3 BT visible on partially healed blaze.</p> <p style="padding-left: 40px;">A spruce, 27 ins. diam., bears N. 11° W., 52 1/2 lks. dist., with partially healed blaze, no marks visible.</p> <p>Continue over nearly level E. slope.</p>
23.10	Top of ascent, slopes N.; desc. 25 ft. over NW. slope.
29.50	Bottom of descent, drains S.; asc. 65 ft. over SE. slope.
30.20	Dirt road, 20 lks. wide, bears N. and S.
36.80	Top of ascent, slopes S.; desc. slightly over SW. slope.
40.88	The N 1/16 sec. cor. of secs. 3 and 4.
	<p>From the NW 1/16 sec. cor. of sec. 3.</p> <p>N. 0° 16' E., on the N 1/2 of the N. and S. center line of the NW 1/4 of sec. 3.</p> <p>Descend 60 ft. over E. slope, changing to broken NE., through moderate timber and dense undergrowth.</p>
23.38	The W 1/16 sec. cor. of secs. 3 and 34, on the N. bdy. of the Tp.
	<p>Subdivision of Section 4, T. 20 S., R. 12 W., Willamette Meridian, Oregon</p>
	<p>From the 1/4 sec. cor. of secs. 4 and 9.</p> <p>N. 0° 17' E., on the N. and S. center line of sec. 4.</p> <p>Ascend slightly over NW. slope, through moderate timber and dense undergrowth.</p>
1.00	Top of ascend, slopes NW.; desc. 160 ft. over broken NE. slope.
10.55	Gravelled road, 25 lks. wide, bears N. 70° W. and S. 70° E.
19.60	Creek, 2 lks. wide, course N. 80° E.; asc. 100 ft. over broken S. slope.