

County Surveyor's Record, Douglas County, Oregon

17141

Subdivision of Sec. 4,
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
20.90	Gravelled road, 20 lks. wide, bears N. 55° W. and S. 55° E.
35.10	Dirt road, 20 lks. wide, bears N. 80° E. and S. 80° W.
40.92	Point for the center 1/4 sec. cor. of sec. 4, at intersection with the E. and W. center line. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> T 20 S R 12 W C 1/4 S 4 1982 </div> from which <div style="margin-left: 40px;"> A hemlock, 15 ins. diam., bears S. 3° E., 39 lks. dist., mkd. C 1/4 S4 BT. A spruce, 17 ins. diam., bears S. 75° W., 34 1/2 lks. dist., mkd. C 1/4 S4 BT. </div> Continue over nearly level land.
61.245	Point for the center N 1/16 sec. cor. of sec. 4. Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with aluminum cap mkd. <div style="text-align: center;"> C N 1/16 S 4 C 1982 </div> from which <div style="margin-left: 40px;"> A spruce, 15 ins. diam., bears S. 1° E., 5 lks. dist., mkd. CN 1/16 S4 BT. A spruce, 10 ins. diam., bears N. 51° W., 8 lks. dist., mkd. X BT. </div> From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor, No. 849, in 1974, bears N. 87° 31' W., 1.335 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. LS 849 C2C HWY 101 1974.
66.00	U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears N. 25° E. and S. 25° W.
83.35	The 1/4 sec. cor. of sec. 4 only, on the N. bdy. of the Tp.
	From the 1/4 sec. cor. of secs. 3 and 4. N. 88° 32' W., on the E. and W. center line of sec. 4. Ascend slightly over SE. slope, through moderate timber and dense undergrowth.
2.00	Top of ascent, slopes S.; desc. 80 ft. over SW. slope.
8.50	Ravine, drains S.; continue over nearly level broken SE. slope.
19.735	Point for the center E 1/16 sec. cor. of sec. 4.