

# County Surveyor's Record, Douglas County, Oregon

17142

Subdivision of Sec. 4,  
T. 20 S., R. 12 W., Willamette Meridian, Oregon

CHAINS	
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C    <math>\frac{E \ 1/16}{S \ 4}</math>    C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A hemlock, 18 ins. diam., bears S. 21° E., 24 lks. dist., mkd. X BT.</p> <p style="padding-left: 40px;">No other suitable trees available.</p> <p>From this point, a point established and recorded by Karl F. Foeste, Registered Land Surveyor No. 849, in 1974, bears S. 88° 51' E., 0.10 chs. dist., monumented with an iron post, 2 ins. diam., firmly set flush with the ground, with brass cap mkd. LS 849 CE 1/16 S4 1974, from which bearing trees mkd. by Foeste:</p> <p style="padding-left: 40px;">A hemlock, 15 ins. diam., bears N. 75° E., 35 lks. dist., with scribe marks CE 1/16 S4 BT visible on open blaze.</p> <p style="padding-left: 40px;">A hemlock, 16 ins. diam., bears N. 47° W., 19 1/2 lks. dist., with scribe marks E 1/16 S4 BT visible on open blaze.</p> <p>Continue over nearly level broken SE. slope.</p>
32.20	Gravelled road, 25 lks. wide, bears N. and S.
38.90	Top of ascent, slopes S.; desc. slightly over SW. slope.
40.06	The center 1/4 sec. cor. of sec. 4.
	Descend 120 ft. over SW. slope.
43.55	Dirt road, 20 lks. wide, bears N. 50° W. and S. 50° E.
53.25	U.S. Highway No. 101, asphalt surface, 50 lks. wide, bears N. 30° E. and S. 30° W.; also bottom of descent, drains S.; asc. 15 ft. over broken SE. slope.
59.19	Point for the center W 1/16 sec. cor. of sec. 4.
	<p>Set an aluminum post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with aluminum cap mkd.</p> <p style="text-align: center;">C    <math>\frac{W \ 1/16}{S \ 4}</math>    C 1982</p> <p>from which</p> <p style="padding-left: 40px;">A pine, 13 ins. diam., bears S. 23° W., 151 1/2 lks. dist., mkd. CW 1/16 S4 BT.</p> <p style="padding-left: 40px;">A fir, 9 ins. diam., bears N. 44 1/2° W., 46 1/2 lks. dist., mkd. CW 1/16 S4 BT.</p> <p>Ascend 45 ft. over broken SE. slope.</p>
71.00	Ridge, bears N. 20° E. and S. 20° W.; desc. 100 ft. over NW. slope.
78.32	The 1/4 sec. cor. of secs. 4 and 5.